


REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	DRAWN BY
N/A	A	WEBSITE DRAWING	2/11/2016	OD
N/A	B	ADDED 20XXSF-XX MODEL NUMBER, NO OTHER CHANGES	10/28/2016	OD
N/A	C	CHANGED P/N TO MPT WAS ADJT, NO OTHER CHANGES.	8/15/2017	OD

HOSE HEIGHT CLEARANCE CHART		
MINIMUM BEND RADIUS "R"	MINIMUM "A"	MINIMUM "B"
2in [50mm]	2 3/4" [70mm]	8 1/2" [216mm]
3in [76mm]	3 3/4" [95mm]	9 1/2" [241mm]
4in [101mm]	4 3/4" [120mm]	10 1/2" [266mm]
5in [127mm]	5 3/4" [146mm]	11 1/2" [292mm]
6in [152mm]	6 3/4" [171mm]	12 1/2" [317mm]
7in [178mm]	7 3/4" [197mm]	13 1/2" [342mm]
NOTE: CLEARANCE WILL SLIGHTLY VARY BASED ON "C" HEIGHT INSTALLATION		



- NOTES:
- FOR EASE OF TILE INSTALLATION, USE LARGEST HOLE RECOMMENDED BY SPRINKLER HEAD MANUFACTURE.

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL=± 1/2 ANGULAR=± 4° BEND=± 4° 1 PLACE DECIMAL[X]= ± 0.030 2 PLACE DECIMAL[XX]= ± 0.020 3 PLACE DECIMAL[XXX]= ± 0.010 INTERPRET GEOMETRIC TOLERANCING PER: ANSI		NAME	DATE	56 Lowland Street, Holliston MA 01746
MATERIAL: N/A		DRAWN BY Admin	02/11/16	www.FlexHead.com 1-800-829-6975
FINISH: N/A		CHECKED BY		TITLE: MPT BRACKET WITH STRAIGHT HOSE(6-1/4" DROP) ASSEMBLY
DO NOT SCALE DRAWING		ENG APPR.		CUST/SUP NAME:
		MFG APPR.		CUST/SUP PART #:
		Q.A. APPR.		SIZE DWG. NO.: C MPT24BKT1-01
		THIRD ANGLE PROJECTION		REV: C
		SCALE: 1:8		SHEET 1 OF 1