



kirei ECHOLINE®

45 PANELS

Etched Acoustic Panels

Energize spaces with dynamic lines that are going places. 45 Panel's simple, consistent groove pattern adds subtle or striking dimension to wall or ceiling surfaces. Easy to install, 45 Panel's controlled playfulness is linear design that fixes acoustic imbalances for happier, healthier occupants.

Product shown: 45 Panels in Color 551 (Duck Egg)

Specs

Style	Standard (LxH)	Thickness	Weight	SF/Panel	Min. Radius
45 (0.5) (12mm)	45.3 in. x 107.5 in.	0.47 in.	19 lbs	35.5	n/a
45 (0.5) (24mm)	45.3 in. x 107.5 in.	0.94 in.	21 lbs	35.5	n/a
45 (1.0) (12mm)	45.3 in. x 107.5 in.	0.47 in.	19 lbs	35.5	n/a
45 (1.0) (24mm)	45.3 in. x 107.5 in.	0.94 in.	21 lbs	35.5	n/a
45 (2.0) (12mm)	45.3 in. x 107.5 in.	0.47 in.	19 lbs	35.5	n/a
45 (2.0) (24mm)	45.3 in. x 107.5 in.	0.94 in.	21 lbs	35.5	n/a
45 (4.0) (12mm)	45.3 in. x 107.5 in.	0.47 in.	19 lbs	35.5	n/a
45 (4.0) (24mm)	45.3 in. x 107.5 in.	0.94 in.	21 lbs	35.5	n/a

All specs refer to singular products and not multiples unless specified. Due to the nature of the material, cutting and fabrication process, minor dimensional variances may occur. Custom options available upon request. 45 Panels are sold individually and ship flat.

Designer	Kirei
Panel Thickness	12mm & 24mm
Material	100% PET (60% post-consumer recycled)
Fire Rating	ASTM E84 Class A
Custom Options	Available upon request
Lead Time	*4-6 weeks (1-100 panels) <i>For larger quantities, lead times determined per order</i>
VOC Emissions	CDPH (CA 01350) Compliant TVOC: <0.5 mg/m ³ Ecospecifier GreenTag Compliant TVOC: 0.015 mg/m ² /hr (ASTM D5116)



Declare.



*Actual lead times are determined when the project goes into production and can change based on production schedule and all quantities, color and thicknesses being in stock at time of order. See [Kirei's Product Lead Time Disclosure](#) for more information.




Acoustic Data





Sound Absorption Groovy 3.0 Panels

Frequency	250Hz	500Hz	800Hz	1000Hz	2000Hz	4000Hz	NRC
m ² /Object	0.22	1.22	2.83	3.66	5.88	7.04	0.40

Acoustic data is measured in Sabins per Groovy 3.0 panel with 12mm thickness.



Product Dimensions



Available Colors



101 Frost
12mm | 24mm



106 Butter
12mm



108 Sunshine
12mm



124 Ochre
12mm | 24mm



167 Cinnamon
12mm | 24mm




193 Rouge
12mm



269 Wine
12mm | 24mm



274 Orchid
12mm | 24mm



276 Lavender
12mm



295 Mandarin
12mm




330 Ivy
12mm | 24mm



338 Jade
12mm



349 Vineyard
12mm



365 Navy
12mm | 24mm




381 Lime Splice
12mm



384 Olive
12mm | 24mm



402 Pebble
12mm | 24mm




442 Grey
12mm | 24mm



444 Smoke
12mm




447 Slate
12mm | 24mm



454 Mushroom
12mm | 24mm



468 Vanilla
12mm | 24mm



484 Cayenne
12mm



487 Blush
12mm | 24mm




495 Dusk
12mm



500 White
12mm | 24mm



542 Black
12mm | 24mm



550 Onyx
12mm | 24mm




551 Duck Egg
12mm




573 Mint
12mm




579 Pistachio
12mm



580 Sage
12mm | 24mm



633 Pacific
12mm | 24mm



660 Coronet
12mm



721 Nutmeg
12mm



908 Cream
12mm | 24mm

Color variation between dye lots is a natural characteristic of recycled PET felt due to the manufacturing process. Slight differences between samples and finished product may occur.

Installation

When mounting, use standard construction adhesives (e.g. Liquid Nails/Titebond - NOT PVA glue). Clean and prepare surface per adhesive guidelines. Spread adhesive evenly on panel back, leaving 2" space at edges. Adhere to wall surface, providing bracing to hold material against surface per adhesive open time/instructions. For more information, see the [EchoLine Panels Installation Guide](#).

Custom Printing with Kirei Ink

45 Panels can be custom printed in house with Kirei Ink. We would love to work with you to print your own custom color, pattern, graphic or material. Reach out and our team will be ready to assist!

Please note: Kirei requires written permission from the copyright holder in order to reproduce any copyrighted work. Professional photographs cannot be reproduced without written permission from the photographer.



Product shown: Diamond Cloud/Tile, Racetrack Path Tile, and Barcode Tile in Kirei Ink (Travertine)



Product shown: 45 (2.0) Panels in Color 274 (Orchid)

kirei

Learn more and request your free sample:

619.236.9924 | sales@kireiusa.com

kireiusa.com