

Specs

Style	Standard (LxH)	Depth	Depth Weight/Unit	
Single Diamond	13.9 in. x 12 in.	6.5 in.	1 lb	0.87
2-Diamond Cluster	13.9 in. x 24.1 in.	6.5 in.	2 lbs	1.74
5-Diamond Cluster	24.4 in. x 36.1 in.	6.5 in.	5 lbs	4.36
10-Diamond Cluster	45.2 in. x 36.1 in.	6.5 in.	10 lbs	8.74

All specs refer to singular products and not multiples unless specified. Due to the nature of the material, cutting and fabrication process, minor dimensional variances may occur.

Designer	Kirei			
Panel Thickness	12mm			
Material	100% PET (60% post-consumer recycled)			
Fire Rating	ASTM E84 Class A			
Custom Options	Available upon request			
Lead Time	*4-6 weeks (1-100 diamonds, not clusters) *6-8 weeks (100+ diamonds, not clusters) For larger quantities, lead times determined per order			
VOC Emissions	CDPH (CA 01350) Compliant TVOC: <0.5 mg/m3 Ecospecifier GreenTag Compliant TVOC: 0.015 mg/m2/hr (ASTM D5116)			

^{*}Actual lead times are determined when the project goes into production and can change based on production schedule and all quantities, color and thicknesses being in stock at time of order. See Kirei's Product Lead Time Disclosure for more information.












Acoustic Data


Sound Absorption

Frequency	250Hz	500Hz	800Hz	1000Hz	2000Hz	4000Hz	NRC
m²/Object	5.27	6.22	5.49	5.72	5.77	6.11	1.05


Acoustic data is measured in Sabins per Diamond Tile.



Product Dimensions



Product Side View



10-Diamond Cluster

Available Colors



Color variation between dye lots is a natural characteristic of recycled PET felt due to the manufacturing process. Slight differences between samples and finished product may occur.

Installation

When mounting, use standard construction adhesives (e.g. Liquid Nails/Titebond - NOT PVA glue). Clean and prepare surface per adhesive guidelines. Spread adhesive evenly on panel back, leaving 2" space at edges. Adhere to wall surface, providing bracing to hold material against surface per adhesive open time/instructions. For more information, see the Diamond Tiles Installation Guide.

Custom Printing with Kirei Ink

Diamond Tiles can be custom printed in house with Kirei Ink. We would love to work with you to print your own custom color, pattern, graphic or material. Reach out and our team will be ready to assist!

<u>Please note</u>: Kirei requires written permission from the copyright holder in order to reproduce any copyrighted work. Professional photographs cannot be reproduced without written permission from the photographer.



Product shown: Diamond Cloud/Tile, Racetrack Path Tile, and Barcode Tile in Kirei Ink (Travertine)



Diamond Tiles in Colors 330 (Ivy) & 365 (Navy)



Product shown: Diamond Tiles in Color 660 (Coronet)



Product shown: Diamond Tiles in Color 444 (Smoke)



Product shown: Diamond Tiles in Colors 124 (Ochre), 365 (Navy), & 349 (Vineyard)

kirei

Learn more and request your free sample: 619.236.9924 | sales@kireiusa.com

kireiusa.com