

## Specs

Style	Standard (LxH)	Depth	Weight/Unit	SF/Unit
EchoStar+	35.8 in. x 31.2 in.	5.5 - 5.7 in.	8 lbs	5.84

All specs refer to singular products and not multiples unless specified. Custom options available upon request. Due to the nature of the material, cutting and fabrication process, minor dimensional variances may occur.

Designer	Kirei			
Panel Thickness	12mm			
Material	100% PET (60% post-consumer recycled)			
Fire Rating	ASTM E84 Class A			
Custom Options	Available upon request			
Lead Time	*4-6 weeks (1-150 EchoStar+)  *6-8 weeks (51-100 EchoStar+)  *8-10 weeks (101-200 EchoStar+)  *12-13 weeks (200+ EchoStar+)  For larger quantities, lead times determined per order			
VOC Emissions	CDPH (CA 01350) Compliant TVOC: <0.5 mg/m3 Ecospecifier GreenTag Compliant TVOC: 0.015 mg/m2/hr (ASTM D5116)			

<sup>\*</sup>Actual lead times are determined when the project goes into production and can change based on production schedule and all quantities, color and thicknesses being in stock at time of order. See <a href="Kirei's Product Lead Time Disclosure">Kirei's Product Lead Time Disclosure</a> for more information.












## **Acoustic Data**


# Sound Absorption


Frequency	250Hz	500Hz	800Hz	1000Hz	2000Hz	4000Hz	NRC
m²/Object	2.84	4.94	5.55	5.79	6.88	7.12	0.50-1.20 determined by installation

Acoustic data is measured in Sabins Sabins per EchoStar+.



# **Product Dimensions**





**Elevation View** 


# **Available Colors**




Color variation between dye lots is a natural characteristic of recycled PET felt due to the manufacturing process. Slight differences between samples and finished product may occur.

#### Installation

Joiners are used to unify EchoStar+ clusters at each adjoining flat edge where two EchoStar+ meet. When ordering multiple EchoStar+ units to be hung in groups, order one Joiner bracket for each pair of edges where EchoStar+'s meet (i.e., one bracket per joint). Each Joiner is supplied with peel-and-stick Velcro ready for application. Peel backer from exposed Velcro and attach adhesive side to EchoStar+ exposed panel. For more information, see the EchoStar+ Installation Guide.




Velcro Placement on Joint



### **Frames**

EchoStar+ frames come standard in white but can be customized to any RAL color as a custom option. EchoStar+ can be ceiling hung using cable and appropriate ceiling mounts. (Ceiling mounts and cable not provided.)



# **Custom Printing with Kirei Ink**

EchoStar+ can be custom printed in house with Kirei Ink. We would love to work with you to print your own custom color, pattern, graphic or material. Reach out and our team will be ready to assist!

<u>Please note</u>: Kirei requires written permission from the copyright holder in order to reproduce any copyrighted work. Professional photographs cannot be reproduced without written permission from the photographer.




Product shown: EchoStar+ in Kirei Ink (Clear Water)




Product shown: EchoStar+ in Color 500 (White) with White frames



Product shown: EchoStar+ in Color 542 (Black) with White frames



Product shown: EchoStar+ in Color 500 (White)



Product shown: EchoStar+ in Color 442 (Grey)



Product shown: EchoStar+ in Color 660 (Coronet) with White frames

# kirei

Learn more and request your free sample: 619.236.9924 | sales@kireiusa.com kireiusa.com