

Specs

Style	Standard (LxH)	Thickness	Weight	SF/Panel
Gem	44.5 in. x 110.2 in.	0.35 in.	17.25 lbs	34
lon	44.5 in. x 110.2 in.	0.35 in.	17.25 lbs	34
Pico	44.5 in. x 110.2 in.	0.35 in.	17.25 lbs	34
Zen	44.5 in. x 110.2 in.	0.35 in.	17.25 lbs	34

All specs refer to singular products and not multiples unless specified. Due to the nature of the material, cutting and fabrication process, minor dimensional variances may occur.

Designer	Woven Image			
Panel Thickness	9mm			
Material	100% PET felt made with at least 51% recycled content.			
Fire Rating	ASTM E84 Class A			
Custom Options	Available upon request			
Lead Time	*In stock for immediate shipment			
VOC Emissions	ASTM D5116 Rate: 0.023 mg/m²/hr (7 days)			

^{*}Actual lead times are determined when the project goes into production and can change based on production schedule and all quantities, color and thicknesses being in stock at time of order. See Kirei's Product Lead Time Disclosure for more information.








Acoustic Data


Sound Absorption

Frequency	250Hz	500Hz	800Hz	1000Hz	2000Hz	4000Hz	NRC
m²/Object	0.40	1.01	2.52	3.43	5.95	7.87	0.30 (no air gap)
m²/Object (20mm air gap)	1.41	4.34	6.66	7.06	7.87	7.87	0.50 (20mm air gap)
m²/Object (50mm air gap)	2.77	6.87	8.72	9.03	9.33	8.82	0.70 (50mm air gap)
m²/Object (50mm panel)	4.17	8.67	10.32	10.43	10.43	9.99	0.75 (50mm panel)

Acoustic data is measured in Sabins per Embossed Panel.



Product Dimensions



Available Colors in Gem



Available Colors in Ion



Available Colors in Pico



Page 6

Available Colors in Zen



Installation

When mounting, use standard construction adhesives (e.g. Liquid Nails/Titebond - NOT PVA glue). Clean and prepare surface per adhesive guidelines. Spread adhesive evenly on panel back, leaving 2" space at edges. Adhere to wall surface, providing bracing to hold material against surface per adhesive open time/instructions. See the Embossed Panel Series Installation Guide for more information.



Product shown: Ion Embossed Panel in Color 124 (Ochre)



Product shown: Pico Embossed Panel in Color 660 (Coronet)




Product shown: Zen Embossed Panel in Color 269 (Wine)




Product shown: Ion Embossed Panel in Colors 550 (Onyx) & 908 (Cream)



Product shown: Gem Embossed Panel in Colors 167 (Cinnamon) & 550 (Onyx)



Product shown: Pico Embossed Panel in Color 274 (Orchid)



Product shown: Zen Embossed Panel in Color 908 (Cream)



Product shown: Gem Embossed Panel in Color 402 (Pebble)

kirei

Learn more and request your free sample: 619.236.9924 | sales@kireiusa.com kireiusa.com

All images in this spec sheet are supplied by Woven Image®.