

I BAFFLES

Acoustic Baffles

I Baffle is an acoustically and visually enhanced extension of Kirei's Simple Baffle. The I Baffle is composed of two 12mm panels attached back-to-back, providing increased acoustic control with an added element of color customization - pick two similar or different panel colors to create new visual effects. Hang I Baffles in regular rows, random groupings, or with other baffle systems to create beautiful architectural design solutions. Custom configurations available.

Product shown: I Baffles in Colors 442 (Grey) & 487 (Blush)

Specs

Style	Standard (LxH)	Width	Weight	LF/Unit
40" Baffle	40 in. x 11.5 in.	0.94 in.	3.5 lbs	3.3
48" Baffle	48 in. x 11.5 in.	0.94 in.	4 lbs	4
72" Baffle	72 in. x 11.5 in.	0.94 in.	6 lbs	6
96" Baffle	96 in. x 11.5 in.	0.94 in.	8 lbs	8

All specs refer to singular products and not multiples unless specified. Due to the nature of the material, cutting and fabrication process, minor dimensional variances may occur.

Designer	Kirei				
Baffle Thickness	24mm				
Material	100% PET (60% post-consumer recycled)				
Fire Rating	ASTM E84 Class A				
Custom Options	Available upon request				
Lead Time	*4-6 weeks (1-100 baffles) *6-8 weeks (150-200 baffles) For larger quantities, lead times determined per order				
VOC Emissions	CDPH (CA 01350) Compliant TVOC: <0.5 mg/m3 Ecospecifier GreenTag Compliant TVOC: 0.015 mg/m2/hr (ASTM D5116)				

^{*}Actual lead times are determined when the project goes into production and can change based on production schedule and all quantities, color and thicknesses being in stock at time of order. See Kirei's Product Lead Time Disclosure for more information.












Acoustic Data


Sound Absorption


Frequency	250Hz	500Hz	800Hz	1000Hz	2000Hz	4000Hz	Average
m²/Object	3.40	4.21	4.71	5.08	5.35	2.23	3.66

Acoustic data is measured in Sabins per I Baffle at 12" spacing.



Product Dimensions





Available Colors




Color variation between dye lots is a natural characteristic of recycled PET felt due to the manufacturing process. Slight differences between samples and finished product may occur.

Installation

The I Baffle's adjustable aluminum channel track hardware makes them even easier to install, level, and align just right. Use a variety of hanging hardware (cable, rod, or direct mount) to work with complex ceiling environments and adjust to existing ceiling obstructions for fast, simple installation. For more information, see the <u>I Baffles Installation Guide</u>.

Note: Kirei does not provide ceiling mounting hardware or cable/chain/rod.



Aluminum Channel Track

Custom Printing with Kirei Ink

I Baffles can be custom printed in house with Kirei Ink. We would love to work with you to print your own custom color, pattern, graphic or material. Reach out and our team will be ready to assist!

<u>Please note</u>: Kirei requires written permission from the copyright holder in order to reproduce any copyrighted work. Professional photographs cannot be reproduced without written permission from the photographer.



Product shown: I Baffles in Colors 442 (Grey) & 487 (Blush)

kirei

Learn more and request your free sample: 619.236.9924 | sales@kireiusa.com kireiusa.com