

Specs

Style	Standard (LxH)	Thickness	Hardware Length	Weight	LF/Unit
40" Baffle	40 in. x 11.5 in.	0.47 in. 0.94 in.	20 - 34 in.	2 lbs 2.5 lbs	3.3
48" Baffle	48 in. x 11.5 in.	0.47 in. 0.94 in.	28 - 42 in.	2.5 lbs 3 lbs	4
72" Baffle	72 in. x 11.5 in.	0.47 in. 0.94 in.	52 - 66 in.	3.75 lbs 4.25 lbs	6
96" Baffle	96 in. x 11.5 in.	0.47 in. 0.94 in.	76 - 90 in.	5 lbs 5.5 lbs	8

All specs refer to singular products and not multiples unless specified. Custom options available upon request. Due to the nature of the material, cutting and fabrication process, minor dimensional variances may occur.

Kirei				
12mm & 24mm				
100% PET (60% post-consumer recycled)				
ASTM E84 Class A				
Available upon request				
*12mm - 4-6 weeks (1-150 baffles) *24mm - 10-12 weeks For larger quantities, lead times determined per order				
CDPH (CA 01350) Compliant TVOC: <0.5 mg/m3 Ecospecifier GreenTag Compliant TVOC: 0.015 mg/m2/hr (ASTM D5116)				

^{*}Actual lead times are determined when the project goes into production and can change based on production schedule and all quantities, color and thicknesses being in stock at time of order. See Kirei's Product Lead Time Disclosure for more information.












Acoustic Data

Sound Absorption Simple Baffle+ (12mm)

Frequency	250Hz	500Hz	800Hz	1000Hz	2000Hz	4000Hz	NRC
m²/Object	0.10	0.22	0.26	0.30	0.47	0.54	0.60

Acoustic data is measured in Sabins per Simple Baffle at 12" spacing.




Acoustic Data


Sound Absorption Simple Baffle+ (24mm)


Frequency	250Hz	500Hz	800Hz	1000Hz	2000Hz	4000Hz	NRC
m²/Object	0.29	0.61	0.89	1.03	1.34	1.32	0.50

Acoustic data is measured in Sabins per Simple Baffle at 28" spacing.



Product Dimensions






Available Colors



Color variation between dye lots is a natural characteristic of recycled PET felt due to the manufacturing process. Slight differences between samples and finished product may occur.

Installation

The Simple Baffle+'s adjustable aluminum channel track hardware makes them even easier to install, level, and align just right. Use a variety of hanging hardware (cable, rod, or direct mount) to work with complex ceiling environments and adjust to existing ceiling obstructions for fast, simple installation. For ACT grid ceilings, Simple Baffle+ can be mounted with T-Grid Clips or magnets, available for an additional charge. For more information, see the Simple Baffle+Installation Guide.







T-Grid Clips

Magnet Mounts

Custom Printing with Kirei Ink

Simple Baffle+ can be custom printed in house with Kirei Ink. We would love to work with you to print your own custom color, pattern, graphic or material. Reach out and our team will be ready to assist!

<u>Please note</u>: Kirei requires written permission from the copyright holder in order to reproduce any copyrighted work. Professional photographs cannot be reproduced without written permission from the photographer.



Product shown: Lipstick Baffles in Kirei Ink (Maze 579)




Product shown: Simple Baffles in Color 274 (Orchid)




Product shown: Custom Simple Baffles in Color 365 (Navy)




Product shown: Capsule Baffles in Color 193 (Rouge)



Product shown: Cutout Baffles in Color 124 (Ochre)



Product shown: Pointed Baffles in Color 444 (Smoke)



Product shown: Lipstick Baffles in Color 487 (Blush)



Product shown: Simple Baffles in Color 542 (Black)

kirei

Learn more and request your free sample: 619.236.9924 | sales@kireiusa.com kireiusa.com