

Specs

Style	Standard Length	Width	Weight	LF/Unit	
Small Pendant	17.75 in.	7.5 in. x 7.09 in.	2 lbs	1.48	
Medium Pendant	26 in.	7.5 in. x 7.09 in.	2 lbs	2.17	
Large Pendant	34.5 in.	7.5 in. x 7.09 in.	3 lbs	2.88	

All specs refer to singular products and not multiples unless specified. Due to the nature of the material, cutting and fabrication process, minor dimensional variances may occur. Baffle lengths can be adjusted up or down in increments of 4.18". The minimum length for a custom sized baffle is 17.72". For longer length rows, baffles can be installed side by side. The lengths will vary slightly due to the complex folded nature of the product and could vary .5"-1.5".

Designer	Kirei			
Panel Thickness	12mm			
Material	100% PET (60% post-consumer recycled)			
Fire Rating	ASTM E84 Class A			
Custom Options	Available upon request			
Lead Time	4-6 weeks (1-100 Pendants)6-8 weeks (100-200 Pendants)For larger quantities, lead times determined per order			
VOC Emissions	CDPH (CA 01350) Compliant TVOC: <0.5 mg/m3 Ecospecifier GreenTag Compliant TVOC: 0.015 mg/m2/hr (ASTM D5116)			

^{*}Actual lead times are determined when the project goes into production and can change based on production schedule and all quantities, color and thicknesses being in stock at time of order. See Kirei's Product Lead Time Disclosure for more information.












Acoustic Data


Sound Absorption


Frequency	250Hz	500Hz	800Hz	1000Hz	2000Hz	4000Hz	NRC
m²/Object	2.57	5.15	6.09	6.28	8.48	9.51	0.70

Acoustic data is measured in Sabins per Tessellate Pendant at 24" spacing.




Product Dimensions









Available Colors



Color variation between dye lots is a natural characteristic of recycled PET felt due to the manufacturing process. Slight differences between samples and finished product may occur.

Installation

Tessellate Pendants are shipped ready to install. Each pendant has three attachment points with preset ¼"-20 male threaded screws. To install Tessellate Pendants, attach ceiling mounting hardware and suspension cable/chain/rod/etc. with the appropriate connector - the supplied Height-adjustable GripLock Cable Set splitter or a different connector of your choice - at the bottom end. Once the ceiling hardware is installed, attach the connector to the supplied attachment hardware on the Tessellate Pendant. Due to the single cable hanging point, we do not recommend hanging Tessellate Pendants in a heavy airflow area as they are susceptible to slight movement once installed. For more information, see the Tessellate Pendants Installation Guide.

Note: Kirei does not provide ceiling mounting hardware or cable/chain/rod.




Cable Splitter Hardware

Custom Printing with Kirei Ink

Tessellate Pendants can be custom printed in house with Kirei Ink. Deliver endless customization possibilities from the natural beauty of botanicals to subtle or striking stonework. Pick from more than 50 prints over Kirei Ink's four collections or print your own custom color, pattern, graphic or material. We would love to work with you. Reach out and our team will be ready to assist!

<u>Please note</u>: Kirei requires written permission from the copyright holder in order to reproduce any copyrighted work. Professional photographs cannot be reproduced without written permission from the photographer. Keep in mind printing is not on the edges of the fully assembled product.



Product shown: Diamond Cloud/Tile, Racetrack Path Tile, and Barcode Tile in Kirei Ink (Travertine)



Product shown: Tessellate Pendants in Color 402 (Pebble)



Product shown: Tessellate Pendants in Color 338 (Jade)

kirei

Learn more and request your free sample: 619.236.9924 | sales@kireiusa.com kireiusa.com