



Mounting Foot Detail

All dimensions shown are in millimetres

All steel construction:

Connections: **1.2m long flying lead (class II)**

Immersion heater rating: **IPX4 or better**

This radiator may only be installed horizontally on floor

Model	Height ± 2mm	Width ± 2mm	Finish	Output Watts	Weight kg
FFZ-190-100/AF	190	1000	painted	500	13.5
FFZ-190-150/AF	190	1500	painted	600	20.4
FFZ-190-200/AF	190	2000	painted	1000	27.3
FFZC-190-100/AF	190	1000	chrome	400	13.5
FFZC-190-150/AF	190	1500	chrome	500	20.4
FFZC-190-200/AF	190	2000	chrome	750	27.3

Issue 1.0

Tools & Material Required

Screws - 4mm diameter x 60mm length
Tape measure
Screwdriver
Electric drill
Masonry drill bit

Key	Component	Qty
A	Screw, 4mm dia x 60mm*	4
* Screws not supplied		

Assembly Instructions

Accurately mark out holes for mounting feet on floor to dimensions as shown on Technical Data Sheet.

Drill four holes to suit screws (A).

Fix radiator to floor with screws (A).

Electric radiators should be fitted only by a qualified electrician and must be earthed and connected to a cable outlet in the bathroom in accordance with I.E.E. wiring regulations. The electrical connection should be made to a '5 amp fused fixed spur' located outside the bathroom.

Note: for maintenance purposes, cable outlets must remain accessible and cables must not be buried directly into walls.

