



## 650 PATIO DOOR

All PVC narrow sash

Our narrow sash 650 patio door makes no compromise on strength. This door features a steel-reinforced sash and wood inserts in the jambs, promising improved durability, smooth operation, and hassle-free installation. With its contemporary style, heightened by a standard aluminum sill cover and jamb pocket covers, this door boasts an exceptional finish that outshines the competition, proving that a PVC sliding door can offer both excellent performance and great design.

650 Patio Door

✕ OPENING PANEL    ○ FIXED PANEL    (EXTERIOR VIEW)

5' WIDTH	6' WIDTH	8' WIDTH	9' & 12' WIDTH	9' & 12' WIDTH	10', 12' & 16' WIDTH
59 1/2" x 79 1/2"	70 1/2" x 81" 71 1/2" x 79 1/2" 71 1/2" x 95 1/2"	95 1/2" x 79 1/2" 95 1/2" x 95 1/2"	107 3/16" x 79 1/2" 107 3/16" x 95 1/2" 143 3/16" x 79 1/2" 143 3/16" x 95 1/2"	107 3/8" x 79 1/2" 107 3/8" x 95 1/2" 143 3/16" x 79 1/2" 143 3/16" x 95 1/2"	116 7/16" x 79 1/2" 140 1/2" x 79 1/2" 140 1/2" x 95 1/2" 188 3/8" x 79 1/2" 188 3/8" x 95 1/2"

Contact your SBP Products distributor for sizing and availability in your region.



**Look Handle (Standard)**

- White
- Black exterior / White interior
- White interior

**View Handle (Option)**

- White
- Black exterior / White interior
- Oil rubbed bronze (Paint)
- Satin Nickel

**Colors**

White (Cream)

Black Exterior (Paint) / White Interior

Custom Color (Option)

**Integrated Blinds**

White

Gray (Option)  
Available Spring 2025

Easy to operate and virtually maintenance free, Integrated Blinds let light in during the day while ensuring absolute privacy at any moment.

Specifications

- Florida Product Approval #FL29466
- TDI Texas Insurance Code approved
- Materials**  
PVC patio door with wood insert in the frame.
- Frame depth** 5 3/4"
- Glazing**  
3/4" Double glazed — Low-E 366 on surface 2,  
U-value: 0.28, SHGC 0.21 US South and South Central  
1" Double glazed — Low-E 366 on surface 2 + IS20,  
U-value: 0.24, SHGC 0.20 US all zones  
1 1/4" Triple glazed — Low-E 366 on surface 2,  
U-value: 0.24, SHGC 0.20 US all zones  
1 1/4" Triple glazed — Low-E 366 on surface 2 and 5,  
U-value: 0.19, SHGC 0.18 US all zones

Options

- A**

  - Jamb pocket cover (Standard)
- B**

  - Anodized aluminum threshold cover (Standard)
  - Double point locking system (Standard)
  - Mosquito screen (Standard)
  - Coastal kit <sup>1</sup>
  - Keylock
  - Keyed alike
- Kick lock
  - Grilles
  - Aluminum sill extension
  - Interior/Exterior PVC jamb extension
  - 1 3/16" frame extension (6 3/16" behind nailing fin)
  - Drywall return
  - Nailing fin (Width behind nailing fin: 4 9/16" or 6 3/16")
- <sup>1</sup> Vanguard handle, stainless steel mortise, keeper and nylon rollers

**Performance**    **Air:** A3    **Water:** 400 Pa (440 Pa with sill tower riser)    **Structural:** DP-55    **Global:** LC-PG55    **STC:** 27    **Door:** 72" x 82"  
(AAMA/WDMA/CSA101/1.S.2/A440-22)

**20-Year** Limited Warranty on Select Components. See the detailed warranty on our website.