


# NoFADE: Analyzing Diminishing Returns on CO2 Investment

*Andre Fu (University of Toronto); Justin B Tran (University of Toronto); Andy Xie (University of Toronto); Jonathan T Spraggett (University of Toronto); Elisa Ding (University of Toronto); Chang-Won Lee (University of Toronto); Kanav Singla (University of Toronto); Mahdi S. Hosseini (University of New Brunswick); Konstantinos N Plataniotis (University of Toronto)*

# Motivation

- Reducing CO2 emissions is essential for curbing climate change effects.
  - IPCC warns that warming of 1.5-2.0°C is likely in the coming decades.
- Previous work on CO2 emission-CV model relationships is not dataset agnostic.
- **NoFADE: Normalized FLOPS for Accuracy-Dataset Entropy**
  - Evaluation metric for model-dataset pair complexity.
  - Show diminishing returns on higher complexity/emissions.



# Diminishing Returns

- Extracted **Top-1 Test-accuracy, mAP or mIOU, FLOPS**, GPU hours and GPU type.
  - 13 Classification, 22 Segmentation, and 10 Detection papers

- Formula for **CV model power draw**:

$$P_m[Wh] = f \times (\omega_g + \omega_c) \times GPU \text{ hours}$$


- **Conversion to emissions:**

$$CO2 = P_m \cdot 0.707 \times 10^{-3}$$


# Diminishing Returns

- Most datasets show accuracy saturation at higher complexity
  - Diminishing returns on CO2 investment


CO2 vs. Test Accuracy (Top-1) on ImageNet




CO2 vs. Test mIoU on CityScape




CO2 vs. Test mAP on COCO



CO2 vs. Test mIoU on PASCAL VOC



CO2 vs. Test mAP on PASCAL





# NoFADE Development


- NoFADE allows for **model-dataset-complexity agnostic comparisons**.
- **Dataset Complexity**
  - **Shannon entropy** (segmentation, detection)
    - $H(image) = -\sum_{i=1}^K p_i \cdot \log p_i$
  - **Sum of Jensen-Shannon distances between classes** (classification)
    - $JSD(P||Q) = \sqrt{\frac{1}{2}D_{KL}(P||M) + \frac{1}{2}D_{KL}(Q||M)}$
- **Relationship between models and datasets**, normalized for computational complexity by log FLOPS:

$$NoFADE = \frac{test\ accuracy \times Entropy\ or\ JSD}{\log FLOPS}$$


# NoFADE: Dataset Complexity

- **Jensen-Shannon distances**
  - CIFAR-10, CIFAR-100
- **Shannon entropy**
  - COCO, Cityscapes, Pascal VOC


CIFAR-10




CIFAR-100




COCO-Stuff



Cityscapes






PASCAL VOC



# NoFADE Results

- **Models with high accuracy and large FLOPS have low NoFADE scores** (eg. ViT transformer models).
  - Complexity cost is penalized.
  - Aim for higher NoFADE scores.



# Conclusion

- Established role of the CV community in global climate change.
- Proposed a metric to track CO2 emissions arising from model training.
- Promote environmental consciousness and model efficiency.
- Encourage researchers to use NoFADE in model-dataset selection to reduce environmental impact.