


SUPPORT DETAIL: UNITS LARGER THAN A 5252 MAY REQUIRE A STIFFENER ACROSS THE WIDTH. A SHADOW MAY BE VISIBLE FROM BELOW.



MODEL CMC2
PYRAMID SHAPE



MODEL CLC2
DOME SHAPE

NFRC CERTIFIED PERFORMANCE

U-FACTOR 0.35
SHGC 0.33

Wasco Part of
VELUX® Commercial

VELUX Wells
85 Spencer Dr, Unit A
Wells, ME 04090
1-800-88-VELUX
veluxusa.com



Skylights pose an inherent risk of injury or death from fall throughs, and the safety of others is of the utmost importance to VELUX. VELUX recommends that the customer, building owner or manager use additional protection with the skylight such as an exterior or interior safety cage, to enhance long-term safety. The building owner or manager is responsible for providing fall protection around the skylight in accordance with OSHA regulations. VELUX also recommends that the building owner or manager restrict roof access only to personnel who have been cautioned as to the location of the skylights, and warned not to sit, step or walk on the skylights.

ORDER #: _____ DATE: _____

PROJECT: _____

LOCATION: _____

CUSTOMER: _____

APPROVED: _____ DATE: _____

MODEL	O.D. OF CURB	QUANTITY
2828	25 1/4" X 25 1/4"	
2852	25 1/4" X 49 1/4"	
3636	33 1/4" X 33 1/4"	
3652	33 1/4" X 49 1/4"	
4242	40" X 40"	
4280	40" X 78"	
5252	49 1/4" X 49 1/4"	
5276	49 1/4" X 72 1/2"	
5296	49 1/4" X 92 1/2"	
5555	51" x 51"	
55102	51" x 99"	
6060	58" X 58"	
6476	60 1/2" X 72 1/2"	
6496	60 1/2" X 92 1/2"	
CUSTOM		

FRAME FINISH: PVC: WHITE

RETAINER FINISH: MILL (STANDARD)

OTHER _____

GLAZING:

OUTER

ACRYLITE® SATIN SKY 2 IR BLOCKING
TRANSLUCENT GLAZING

INNER

LUMIRA™ AEROGEL FILLED 10mm
MULTIWALL POLYCARBONATE PANEL

CLC2/CMC2-DOUBLE DOME-NFRC CERTIFIED CURB MOUNT

DATE:
05/2019

DRAWING NO.:
CLC2 / CMC2

REV 0
SHEET 1 OF 1