

- 2. The architectural/structural design and specifications for the inclusion of a commercial skylight, such as the VELUX DMT1 in any roofing/ceiling application is determined and provided by others. The design criteria includes, but is not limited to design loads, structural configurations, structural framing member sizes and material, architectural finishes and integration with the roofing/ceiling systems of the building. VELUX recommends compliance by all designers and installers with all local and industry specific building codes and guidelines. VELUX assumes no responsibility or liability in the design, construction and performance of a building structure by others.
- The fasteners securing the curb to the rough opening are provided by others. VELUX recommends #8 x 1-3/4" steel non-corrosive fasteners. The fasteners should be placed in the center of the curb flange 4" from each corner and 12" on center for the length and width of the deck mounted skylight.

This drawing is an instrument of service and is provided for informational use only.

Sky-Global Product Management

1418 Evans Pond Road Greenwood, SC 29649 1-800-88-VELUX www.VELUXUSA.com

DMT1 Deck Mount Traditional Single Dome Skylight

Traditional Single Dome Options Size - Width x Length (using Inside Curb Dimensions) Quantity Dome Description and Designation Material\* LuxGuard ).118" Polycarbonat

\*Note: Dome Material thickness is sheet material's thickness prior to the manufacturing process

12"

9"

Frame Finish Options Neutral Gray Powder Coat Standard Curb Heights

16"

**Product Dimension** 

(Inside Curb Dimension +  $5\frac{1}{2}$ ")

**SECTION B-B**