

B-10083 E

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1. SDS Revision Date: 11/2/2018

	1. PRODUCT & COMPANY IDENTIFICATION					
1.1	Product Name:	Sexy Hair Foam Party				
1.2	Chemical Name:	Aerosol Foam				
1.3	Synonyms:	Pacific Coast Texture Foam – B-10083E				
1.4	Trade Names:	Sexy Hair Pacific Coast Texture Foam				
1.5	Product Uses & Restrictions	Professional and Cosmetic Use				
1.6	Distributor's Name:	KIK Custom Products				
1.7	Distributor's Address:	2030 Old Candler Road, Gainesville, GA 30507 USA				
1.8	Emergency Phone:	CHEMTEL: +1 (703) 527-3887 / +1 (800) 424-9300				
1.9	Business Phone / Fax:	+1 (770) 534-0300 / +1 (770) 534-8954				
	2. HAZARDS IDENTIFICATION					
2.1	Hazard Identification:	This product is classified as a HAZARDOUS by the 2012 OSHA Hazard Communication Standard				

(29CFR 1910.1200)

WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION.

Classification: Level 1 Aerosol; Category 2 Flammable Aerosol

Hazard Statements:

Flammable Aerosol- Category 2 Gases under Pressure – Liquefied Gas

Causes eye irritation -Category 2 - Sub category B

Precautionary Statement (P): Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Precautionary Statements - response: Avoid breathing vapors/spray. Use only in well-ventilated area. IF INHALED; Remove person to fresh air and keep comfortable for breathing. IF IN EYES; Rinse cautiously with water for several minutes. Remove contact lenses, if present, continue rinsing. If eye irritation persists: Get medical advice/attention.

Precautionary Statements - Storage: Protect from sunlight. Do no expose to temperature exceeding 48°C (120 °F). Keep product locked up and out of reach of children. Store in well ventilated areas.

Precautionary Statements - Disposal: Dispose of contents/container to licensed and permitted disposal or recycling facility.

Hazards not otherwise classified (HNOC)

Not Applicable



3. COMPOSITION & INGREDIENT INFORMATION

Substance / Chemical Name(s)	CAS No.	EINECS No.	%	Other
ISOBUTANE	75-28-5	200-857-2	1 - 5	Flam. Gas 1; H220
PROPANE	74-98-6	200-827-9	0.1 - 5	Press. Gas 1; Flam. Gas 1; H220

4. FIRST AID MEASURES

4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Skin:	If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before ruse. If irritation, redness or swelling persists, consult a physician immediately.
		Eyes:	If product get in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Raise and lower eyelid(s) while flushing to ensure thorough irrigation. If problems persist seek immediate medical attention.
		Inhalation:	Remove victim to fresh air and keep comfortable for breathing.



B-10083 E

4.2	Effects of Exposure:	Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.								
		May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals upon prolonged or repeated exposure.								
		Eyes: Moderately irritating to the eyes.								
		Vapors of this product may be moderately irritating to the nose, throat and other tissues of the								
		Inhalation:	respiratory system. Symptoms of overexposure c		-					
		minaration.	and difficulty breathing. Inhalation of concentrate	ed vapors can cause nervous syst	em depression					
			(e.g., drowsiness, dizziness, headaches, nausea).							
4.3	Symptoms of Overexposure	Ingestion:								
		Prolonged contact with skin may result in bleaching and irritation of skin. The product can cause Skin: allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Symptoms of skin								
		Skin:			Symptoms of skin					
			overexposure may include redness, itching, and in		mage to eyes)					
		Eyes:	Overexposure in eyes, may cause redness, itching and watering (risk of serious damage to eyes) Contact may cause mild eye irritation including stinging, watering and redness.							
		Inhalation:	Symptoms of overexposure can include coughing, breathing.	wheezing, nasal congestion, and	l difficulty					
	A such a Line like Effective	Moderate irrita	tion to eyes and skin near affected areas. Additional	ally, high concentrations of vapor	 of vapors can cause					
4.4	Acute Health Effects:		ziness, headaches and nausea.							
			chronic health effects are expected to occur from a s	-	-					
4.5	Chronic Health Effects:	_	skin and mucous membrane of the eye and respirat							
		allergic dermat	symptoms in some sensitive individuals. May also induce skin sensitization and respiratory hypersensitivity. Possible							
4.6	Target Organs:	Eyes, skin, resp								
4.7	Medical Conditions		azards may be delayed. Most common symptoms	HEALTH	1					
	Aggravated by Exposure	l	g properties to eyes, respiratory system and skin.	FLAMMABILITY	3					
	7.66.44464 27 2.76644.6	Existing dermat	0							
			10.06.0a. 00.1a.t.01.5 (5a.0.1 a5 cozea) a.ra	PHYSICAL HAZARDS	-					
		_	ditions (such as bronchial asthma and/or	PROTECTIVE EQUIPMENT	В					
		respiratory con			-					
		respiratory con	ditions (such as bronchial asthma and/or	PROTECTIVE EQUIPMENT	-					
		respiratory con	ditions (such as bronchial asthma and/or	PROTECTIVE EQUIPMENT	-					
5.1	Fire and Explosion Hazards:	respiratory con bronchitis) may Level 1 Aerosol	ditions (such as bronchial asthma and/or be exacerbated. 5. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a	PROTECTIVE EQUIPMENT EYES SKIN bove 120° F. Cool uninvolved	-					
5.1	Fire and Explosion Hazards:	respiratory con bronchitis) may Level 1 Aerosol containers to p	ditions (such as bronchial asthma and/or be exacerbated. 5. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile	PROTECTIVE EQUIPMENT EYES SKIN bove 120° F. Cool uninvolved e hazards when bursting. If	-					
5.1	Fire and Explosion Hazards:	respiratory con bronchitis) may Level 1 Aerosol containers to p aerosols are bu	ditions (such as bronchial asthma and/or be exacerbated. 5. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Contain	bove 120° F. Cool uninvolved be hazards when bursting. If thers may rupture and release	-					
5.1	Fire and Explosion Hazards:	Level 1 Aerosol containers to p aerosols are bu flammable liqu	ditions (such as bronchial asthma and/or be exacerbated. 5. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile reting, stay clear until bursting is complete. Containids and/or exposed gases if exposed to the heat of f	bove 120° F. Cool uninvolved be hazards when bursting. If thers may rupture and release	-					
	·	Level 1 Aerosol containers to p aerosols are bu flammable liqu spraying them	ditions (such as bronchial asthma and/or be exacerbated. 5. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile reting, stay clear until bursting is complete. Containids and/or exposed gases if exposed to the heat of f with water until the fire has been extinguished.	bove 120° F. Cool uninvolved be hazards when bursting. If thers may rupture and release	-					
5.2	Extinguishing Methods:	Level 1 Aerosol containers to p aerosols are bu flammable liqu spraying them.	ditions (such as bronchial asthma and/or be exacerbated. 5. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile reting, stay clear until bursting is complete. Contain ids and/or exposed gases if exposed to the heat of f with water until the fire has been extinguished. m, CO ₂ , Dry Chemical	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by	-					
5.2	·	Level 1 Aerosol containers to p aerosols are bu flammable liqu spraying them. Water Fog, Foa As in any fire, v	ditions (such as bronchial asthma and/or be exacerbated. 5. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile reting, stay clear until bursting is complete. Containids and/or exposed gases if exposed to the heat of f with water until the fire has been extinguished.	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by	-					
5.2	Extinguishing Methods:	Level 1 Aerosol containers to p aerosols are bu flammable liqu spraying them. Water Fog, Foa As in any fire, w demand_ and f	ditions (such as bronchial asthma and/or be exacerbated. 5. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Contain ids and/or exposed gases if exposed to the heat of f with water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by	-					
5.2	Extinguishing Methods:	Level 1 Aerosol containers to p aerosols are bu flammable liqu spraying them. Water Fog, Foa As in any fire, w demand_ and f spray to cool fire	ditions (such as bronchial asthma and/or be exacerbated. 5. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Contain ids and/or exposed gases if exposed to the heat of f with water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathinull protective gear. Keep containers cool until well is	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by	-					
5.1 5.2 5.3	Extinguishing Methods:	Level 1 Aerosol containers to p aerosols are bu flammable liqu spraying them. Water Fog, Foa As in any fire, v demand_ and f spray to cool fit from fire controwaterway. Fire	ditions (such as bronchial asthma and/or be exacerbated. 5. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Contained and/or exposed gases if exposed to the heat of fwith water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing ull protective gear. Keep containers cool until well are-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking efighters must use full bunker gear including NIOSH-	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by apparatus (pressure-after the fire is out. Use water the upwind. Prevent runoff water supply, or any natural approved positive pressure self-	-					
5.2	Extinguishing Methods:	Level 1 Aerosol containers to p aerosols are bu flammable liqu spraying them. Water Fog, Foa As in any fire, v demand_ and f spray to cool fir from fire controwaterway. Fire contained brea	ditions (such as bronchial asthma and/or be exacerbated. 5. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Contained and/or exposed gases if exposed to the heat of fixed water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing ull protective gear. Keep containers cool until well are-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking of dilution from entering sewers, drains, drinking stighters must use full bunker gear including NIOSH-thing apparatus to protect against potential hazardo	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by apparatus (pressure-after the fire is out. Use water the upwind. Prevent runoff water supply, or any natural approved positive pressure self-	-					
5.2	Extinguishing Methods:	Level 1 Aerosol containers to p aerosols are bu flammable liqu spraying them. Water Fog, Foa As in any fire, v demand_ and f spray to cool fir from fire controwaterway. Fire contained brea	ditions (such as bronchial asthma and/or be exacerbated. 5. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Contained and/or exposed gases if exposed to the heat of fwith water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing ull protective gear. Keep containers cool until well are-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking efighters must use full bunker gear including NIOSH-	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by apparatus (pressure-after the fire is out. Use water the upwind. Prevent runoff water supply, or any natural approved positive pressure self-	-					
5.2	Extinguishing Methods:	Level 1 Aerosol containers to p aerosols are bu flammable liqu spraying them. Water Fog, Foa As in any fire, w demand_ and f spray to cool fir from fire control waterway. Fire contained brea decomposition	S. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Containids and/or exposed gases if exposed to the heat of f with water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathinull protective gear. Keep containers cool until well are-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking efighters must use full bunker gear including NIOSH-thing apparatus to protect against potential hazardo products and oxygen deficiencies.	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by apparatus (pressureafter the fire is out. Use water tire upwind. Prevent runoff water supply, or any natural approved positive pressure self-bus combustion or	-					
5.2	Extinguishing Methods: Firefighting Procedures:	Level 1 Aerosol containers to p aerosols are bu flammable liqu spraying them. Water Fog, Foa As in any fire, v demand_ and f spray to cool fit from fire control waterway. Fire contained brea decomposition	S. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Contain ids and/or exposed gases if exposed to the heat of f with water until the fire has been extinguished. m, CO ₂ , Dry Chemical vear MSHA/NIOSH approved self-contained breathin ull protective gear. Keep containers cool until well are-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking of or dilution from entering severs, drains, drinking of the products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible projectile.	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by apparatus (pressure-after the fire is out. Use water the fire upwind. Prevent runoff water supply, or any natural approved positive pressure self-bus combustion or	B 3 0					
5.2	Extinguishing Methods:	Level 1 Aerosol containers to p aerosols are but flammable liquing spraying them. Water Fog, Foa As in any fire, videmand_ and find spray to cool fit from fire contrivaterway. Fire contained brea decomposition	S. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Contained and/or exposed gases if exposed to the heat of fwith water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing ull protective gear. Keep containers cool until well are-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking effighters must use full bunker gear including NIOSH-thing apparatus to protect against potential hazarded products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASURA (See Product of Spill cleanure)	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by apparatus (pressure-after the fire is out. Use water the fire upwind. Prevent runoff water supply, or any natural approved positive pressure self-bus combustion or	B 3 0					
5.2	Extinguishing Methods: Firefighting Procedures:	Level 1 Aerosol containers to p aerosols are but flammable liquing spraying them. Water Fog, Foa As in any fire, videmand_ and find spray to cool fit from fire controlled breadecomposition. Before cleaning Equipment (PPI)	S. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Contained and/or exposed gases if exposed to the heat of fwith water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing ull protective gear. Keep containers cool until well are-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking of or dilution from entering sewers, drains, drinking apparatus to protect against potential hazarded products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASURE in the product of the produ	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by apparatus (pressureafter the fire is out. Use water tire upwind. Prevent runoff water supply, or any natural approved positive pressure self-bus combustion or	B 3 0					
5.2	Extinguishing Methods: Firefighting Procedures:	Level 1 Aerosol containers to p aerosols are but flammable liquing spraying them. Water Fog, Foa As in any fire, videmand_ and find spray to cool fit from fire contained brea decomposition Before cleaning Equipment (PPI Small spills Wester Small spills Small spills Wester Small spills Wester Small spills Wester Small spills Small spill s	S. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Contained and/or exposed gases if exposed to the heat of fwith water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing ull protective gear. Keep containers cool until well are-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking effighters must use full bunker gear including NIOSH-thing apparatus to protect against potential hazarded products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASURA (See Product of Spill cleanure)	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by apparatus (pressure-after the fire is out. Use water tire upwind. Prevent runoff water supply, or any natural approved positive pressure self-ous combustion or	al Protective					
5.2	Extinguishing Methods: Firefighting Procedures:	Level 1 Aerosol containers to p aerosols are but flammable liquing spraying them. Water Fog, Foa As in any fire, videmand_ and find spray to cool fit from fire control waterway. Fire contained brea decomposition Before cleaning Equipment (PPI Small spills West combustible may bronch the spray to combustible may be some the spills west combustible may be some the spills we spill the spills west combustible may be some the spills we spill the spilling the spill the spill the spill the spill the spill the spill t	S. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Contained sand/or exposed gases if exposed to the heat of fwith water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing ull protective gear. Keep containers cool until well are-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking of or dilution from entering sewers, drains, drinking of or dilution from entering sewers. 6. ACCIDENTIAL RELEASE MEASURES any spill or leak, individuals involved in spill cleanures.	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by apparatus (pressureafter the fire is out. Use water the upwind. Prevent runoff water supply, or any natural approved positive pressure selfous combustion or	al Protective ear. Use a non-for later disposal.					
5.2	Extinguishing Methods: Firefighting Procedures:	Level 1 Aerosol containers to p aerosols are bu flammable liquing spraying them. Water Fog, Foa As in any fire, with demand_ and fire spray to cool fire from fire control waterway. Fire contained bread decomposition Before cleaning Equipment (PPI Small spills West combustible materials (e.g.,	S. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Contained and/or exposed gases if exposed to the heat of fwith water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing ull protective gear. Keep containers cool until well are-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking effighters must use full bunker gear including NIOSH-thing apparatus to protect against potential hazarded products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASURE and spropriate personal protective equipment includaterial such as vermiculite or sand to soak up the products and to soak up the products and syermiculite or sand to soak up the products and source of the products and to soak up the products and syermiculite or sand to soak up the products and source of the products and to soak up the products are specifically as a suppropriate personal protective equipment includaterial such as vermiculite or sand to soak up the products and source of the products and to soak up the products and source of the products and to soak up the products are specifically as a suppropriate personal protective equipment includates and the products and to soak up the products and source of the products and to soak up the products are specifically as a suppropriate personal protective equipment includes a specifically as a suppropriate personal protective equipment includes a specifically as a specifical specifica	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by Ing apparatus (pressure-after the fire is out. Use water tire upwind. Prevent runoff water supply, or any natural approved positive pressure self-bus combustion or IRES p must wear appropriate Personating gloves and protective eyewed oduct and place into a container terial. Sweep up material using research in the protective eyewed oduct and place into a container terial. Sweep up material using research in the protective eyewed oduct and place into a container terial. Sweep up material using research in the protective eyewed oduct and place into a container terial.	al Protective ear. Use a non- for later disposal. non-sparking					
5.2	Extinguishing Methods: Firefighting Procedures:	Level 1 Aerosol containers to p aerosols are bu flammable liqu spraying them. Water Fog, Foa As in any fire, w demand_ and f spray to cool fir from fire control waterway. Fire contained brea decomposition Before cleaning Equipment (PPI Small spills West combustible materials (e.g., container.	S. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile risting, stay clear until bursting is complete. Containids and/or exposed gases if exposed to the heat of f with water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing ull protective gear. Keep containers cool until well a re-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking effighters must use full bunker gear including NIOSH-thing apparatus to protect against potential hazardo products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASURA any spill or leak, individuals involved in spill cleanural appropriate personal protective equipment includaterial such as vermiculite or sand to soak up the prier or a material such as "speedy dry" to soak up ma plastic brooms, shovels, dustpans) and place into a	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by apparatus (pressureafter the fire is out. Use water tire upwind. Prevent runoff water supply, or any natural approved positive pressure selfous combustion or apparatus expensive pressure selfous combustion or bust wear appropriate Personal ding gloves and protective eyewed oduct and place into a container terial. Sweep up material using a plastic container or plastic liner of the service of the ser	al Protective ear. Use a non- for later disposal. non-sparking within another					
5.2	Extinguishing Methods: Firefighting Procedures:	Level 1 Aerosol containers to p aerosols are bu flammable liquingraying them with the series of the	S. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile risting, stay clear until bursting is complete. Containids and/or exposed gases if exposed to the heat of f with water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathinull protective gear. Keep containers cool until well a re-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking efighters must use full bunker gear including NIOSH-thing apparatus to protect against potential hazardo products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASURES and so yellow the proposition of the proposit	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by apparatus (pressureafter the fire is out. Use water tire upwind. Prevent runoff water supply, or any natural approved positive pressure self-bus combustion or apparatus expensive pressure self-bus combustion or bust wear appropriate Personal ding gloves and protective eyewed oduct and place into a container terial. Sweep up material using replastic container or plastic liner was away from spill. Stay upwind and away from spill. Stay upwind and analysis is self-bus container or plastic liner was away from spill. Stay upwind and away from spill. Stay upwind and analysis is self-bus container or plastic liner was away from spill. Stay upwind and analysis is self-bust or plastic liner was away from spill. Stay upwind and analysis is self-bust or plastic liner was away from spill. Stay upwind and self-bust or plastic liner was away from spill. Stay upwind and self-bust or plastic liner was away from spill. Stay upwind and self-bust or plastic liner was away from spill. Stay upwind and self-bust or plastic liner was away from spill. Stay upwind and self-bust or plastic liner was away from spill. Stay upwind and self-bust or plastic liner was away from spill.	al Protective ear. Use a non- for later disposal. non-sparking within another and away from spill of					
5.2	Extinguishing Methods: Firefighting Procedures:	Level 1 Aerosol containers to p aerosols are bu flammable liquispraying them. Water Fog, Foa As in any fire, widemand_ and fispray to cool find from fire control waterway. Fire contained breat decomposition Before cleaning Equipment (PPI Small spills West combustible materials (e.g., container. Large spills: Keerrelease. Isolater	S. FIREFIGHTING MEASURES (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile risting, stay clear until bursting is complete. Containids and/or exposed gases if exposed to the heat of f with water until the fire has been extinguished. m, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing ull protective gear. Keep containers cool until well a re-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking effighters must use full bunker gear including NIOSH-thing apparatus to protect against potential hazardo products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASURA any spill or leak, individuals involved in spill cleanural appropriate personal protective equipment includaterial such as vermiculite or sand to soak up the prier or a material such as "speedy dry" to soak up ma plastic brooms, shovels, dustpans) and place into a	bove 120° F. Cool uninvolved e hazards when bursting. If hers may rupture and release ire. Keep containers cool by apparatus (pressureafter the fire is out. Use water tire upwind. Prevent runoff water supply, or any natural approved positive pressure self-bus combustion or busting gloves and protective eyewed oduct and place into a container terial. Sweep up material using replastic container or plastic liner was away from spill. Stay upwind and sonnel out of area. Stop spill or	al Protective ear. Use a non- for later disposal. non-sparking within another and away from spill of release if it can be					



B-10083 E

		7. HAN	DLING A	AND STO	RAGE I	NFORM	OITAN	1			
		Do not eat, drink, or	smoke whil	e handling th	is product.	Contents	under press	sure. Ha	andle as to	avoid p	uncturing
7.1	Work & Hygiene Do not eat, drink, or smoke while handling this product. Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if 6						-				
	Practices	contact is possible. Wash unintentional residues with soap and warm water.									
		Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct									
7.2	Storage and Handling:	sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from									
		physical damage. To	avoid unint	tentional spra	ying, keep	cap in plac	e when not	t in use.	Storage I	evel 2.	
7.3	Special Precautions:	Spilled material may	present a sl	lipping hazard	l if left unat	tended. C	lean all spil	ls prom	ptly.		
		8. EXPOSU	RE CON	TROLS &	PERSO	NAL P	ROTECT	ΓΙΟΝ			
8.1	Exposure Limits:		A	CGIH		NOHSC		(DSHA	OTHER	
	Ppm (mg/m ³)										
			TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		Chemical Name(s)									
		ISOBUTANE	600	750	NF	NF	NA	NA	NA	NA	
		PROPANE	1000	NA	1000	NF	NF	1000	NA	2100	
8.2	Ventilation &	General mechanical									or general
Ī	Engineering Controls	exhaust ventilation									
		product.	•	•	•	•	•	Ū			· ·
8.3	Respiratory Protection:	No special respirato	ry protection	n is required i	under typica	al circumst	ances of us	e or ha	ndling.		
		In instances where o	lusts of this	product are g	enerated, a	nd respira	tory protec	ction is r	needed,		
		use only protection	authorized b	y 29 CFR §19	10.134, app	licable U.S	S. State reg	ulations	, or the		
		Canadian CAS Stand	ard Z94.4-93	3 and applicat	ole standard	ls of Canad	dian Provin	ces, EC ı	member		
		States, or Australia.									
8.4	Eye Protection:	None required unde							uld be	/	
		used when handling	or using lar	ge quantities	of this prod	uct (e.g., <u>></u>	≥ 1 gallon (3	3.8 L)).			
8.5	Hand Protection:	None required unde	r normal co	aditions of us			co chin irrit	ation is			
0.5	nana Protection.	sensitive individuals									M)
		nitrile or impervious			idilities (c.	5., <u>~</u> 1 gain)II (3.0 L)), '	wcarra	bbci,		Lu S
			P								
8.6	Body Protection:	No apron required v	vhen handlir	ng small quan	tities. Whe	n handling	large quar	itities (e	e.g., > 5		
	,	lbs.), eye wash statio									
		activities involving la	arge quantiti	ies of this pro	duct, wash	any expos	ed areas th	oroughl	y with		
		soap and water.									
		9. P	HYSICAI	L & CHEN	/IICAL P	ROPE	RTIES				
9.1	Appearance:	Aerosol, white foam									
9.2	Odor:	Fresh Floral									
9.3	Odor Threshold	NA									
9.4	pH:	4.5 – 6.5									
9.5	Melting/Freezing Point	NA									
9.6	Initial Boiling Point/	NA									
	Boiling Range:										
9.7	Flashpoint:	-30 °F (-34 °C) TCC fo	or propellant	t only.							
9.8	Upper/Lower	NA									
0.0	Flammability limits	@ 20 °C (C0° F)	n nrc	at to a	100:- 0	FF %C /434	°F\ 43 4 !				
9.9	Vapor Pressure:	@ 20 °C (68° F) – Ca	n pressure n	ot to exceed	TAN beig @	oo C(131	r) 12.4 ba	II.			
	Vapor Density	>1									
	Relative Density:	095 – 1.005 Soluble									
	Solubility: Partition Coefficient	NA									
5.13		INA									
9 1/1	(log Pow): 14 Autoignition NA										
J.14	Temperature:	l vo									



B-10083 E

9 15	Decomposition	NA					
3.13	Temperature.						
9.16	Viscosity:	Aerosol at ambient temperature					
9.17	Other Information:	Evaporation Rate >1: Percent Volatile 6%					
		27dportation Nate / 211 Greene Volume 0/0					
		10. STABILITY & REACTIVITY					
10.1	0.1 Stability: Stable at normal temperatures.						
	Hazardous						
	Decomposition	Oxides of carbon (CO, CO ₂) and sulfur (SO ₂)					
	Products:	· · · · · · · · · · · · · · · · · · ·					
10.3	Hazardous	MGII and annua					
	Polymerization:	Will not occur.					
	Conditions to Avoid	Excessive heat, direct sunlight, flames, heat sources and incompatible substances.					
10.5	Incompatible Substances	Mixture with strong acids, alkalis or oxidizers.					
		11. TOXICOLOGICAL INFORMATION					
11 1	Routes of Entry:	Inhalation: YES Absorption: YES Ingestion: YES					
	Toxicity Data:	This product was not tested on animals. Toxicology data, found in scientific literature, is available and not presented in					
11.2	Toxicity Data.	this document.					
11.3	Acute Toxicity:	See Section 4.4					
	Chronic Toxicity:	See Section 4.5					
11.5	Suspected Carcinogen:	No.					
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.					
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.					
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.					
	Teratogenicity:	This product is not report to cause teratogenic effects in humans.					
	Reproductive Toxicity:	This product is not report to cause reproductive effects in humans.					
11.7	Irritancy of Product:	See Section 4.3					
11.8	Biological Exposure Indices:	NA NA					
11.9	Physician Recommendations:	Treat symptomatically.					
		12. ECOLOGICAL INFORMATION					
12.1	Environmental Stability:	There is no specific data available for this product.					
12.2	Effects on Plants & Animals	There is no specific data available for this product.					
12.3	12.3 Effects on Aquatic Life: The product itself has not been tested as a whole. There is no specific data available for this product.						
		13. DISPOSAL CONSIDERATIONS					
13.1	, , , , , , , , , , , , , , , , , , ,						
		appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with					
	local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed						
42.2	facility or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.						
13.2	Special Considerations:	U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001)					
	14. TRANSPORTATION INFORMATION						
14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L); or					
		CONSUMER COMMODITY, ORM-D (IP VOL \leq 1.0 L) – until 12/31/2020					
14.2	IATA (AIR)	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL < 0.5 L); or					
		ID8000, CONSUMER COMMODITY, ORM-D (IP VOL < 0.5 l=L)					
	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L)					
14.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L); or					
\sqcup		MARK PACKAGE "LIMITED QUANTITY", "LTD QTY", OR "QUANT LTÉE" OR "QUANTITÉ LIMITÉE"					
$\overline{}$	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL <u>1.0 L</u>)					
	SCT (MEXICO):	UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL < 1.0 L)					
14./	4.7 ADGR (AUS): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL <u>< 1.0 L)</u>						



B-10083 E


		15. REGULATORY INFORM	IATION					
15.1	SARA Reporting Requirements:	This product does not contain any substance subject to SATA Title III, section 313 reporting requirements.						
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.						
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.						
15.4	CERCLA Reportable Quantity (RQ):	NA NA						
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G. (Cosmetics)						
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of the product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substance List. WHMIS Class B5 (Flammable Aerosol)						
15.7	State Regulatory Information:	Isobutane is found on the following state criteria lists: Mass Right-to-Know list (PA), New Jersey Right-to-Know List (NJ) Propane can be found on the following state criteria lists: N						
		No other ingredients of this product, present in a concentral state criteria lists: California Proposition 65 (CA65), Delawa Substances List (FL), Massachusetts Hazardous Substances Hazardous Substances List (MN), New Jersey Right-to-Know Pennsylvania Right-to-Know List (PA), Washington Permissil List (WI).	re Air Quality Management List (DE), Florida Toxic List (MA), Michigan Critical Substances List (MI), Minnesota List (NJ), New York Hazardous Substances List (NY), ble Exposures List (WA), Wisconsin Hazardous Substances					
15.8	Other Requirements:	The primary components of this product are listed in Annex Isobutane: Flammable (F). Risk Phrases (R) 12 — Highly Fla Keep out of reach of children. Keep container in a well-ven sources of ignition — No smoking. Propane: : Flammable (F). Risk Phrases (R) 12 — Highly Flam Keep out of reach of children. Keep container in a well-ven sources of ignition — No smoking.	mmable. Safety Phrases (S): 2-9-16 – tilated area. Keep away from mmable. Safety Phrases (S): 2-9-16 –					
		16. OTHER INFORMAT	ION					
16.1	Other Information:		INER: MAY BURST IF HEATED, HIGHLY FLAMMABLE LIQUID eat, hot surfaces, sparks open flames and other ignition ther ignition source. Do not pierce or burn, even after use, and water after handling. Use only in a well ventilated area. To temperature exceeding 50 °C (122 °F). IF INHALED: hing. IF IN EYES: Rinse cautiously with water for several					
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.						
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the base of KIK Custom Product's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or complete=ness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.						
16.4	Prepared By:	KIK Custom Products 2030 Old Candler Road Gainesville, GA 30507 USA http://www.kikcorp.com	KIK CUSTOM PRODUCTS					



B-10083 E

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.

SDS Revision Date: 11/2/2018





B-10083 E

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.

SDS Revision Date: 11/2/2018

