



BANISH

BANISH 30 GOLD-V2 OWNER'S MANUAL

BANISH Suppressors has always had one overriding goal in mind - to make the most user-friendly suppressor on the market. And what is more user-friendly than being multi-caliber and user-serviceable? At BANISH Suppressors, we are proud of what we've accomplished, and we want to share with you what makes a BANISH Suppressor stand out from the crowd.

Our unique WhisperTech™ tube is where the BANISH multi-caliber system starts, with a lightweight titanium alloy tube. BANISH Suppressors are light-weight and tough enough for a lifetime of service. The internal baffles handle the gas in such a way that the suppressor significantly reduces recoil as well as sound. Cleaning your can isn't a problem with our CanClean™ technology, making this one of the fastest cleaning suppressors on the market.



WARNING

To provide for your safety and the effective use of this silencer, it is important that the owner and any user of the silencer read this entire manual and strictly follow the warnings and instructions within. This silencer should be used only by those who are well-versed in the safe operation of firearms.

Failure to follow installation and maintenance instructions in this manual may result in serious personal injury and damage to the firearm.

Suppressed firearms make less noise than unsuppressed firearms and it is easy to forget that they are still capable of causing bodily injury and property damage. Remember, a suppressed firearm should be treated with the same safety and caution as an unsuppressed firearm.

Before installing the silencer, be sure that the firearm is unloaded and the action is opened and visibly clear of any ammunition. If you are at all unsure as to the proper procedures to ensure that your firearm is unloaded, please consult your firearm user's manual/instructions and/or contact a properly licensed dealer or the manufacturer of your firearm.

Firearm silencers are user-attached firearm muzzle devices, and as such are subject to improper attachment issues unless the procedures outlined in this manual are followed precisely.

Check the fit between your barrel and silencer before firing! The thread mount must be fully shouldered on the barrel. There should be no visible gap between the barrel shoulder and the face of the silencer thread mount (crush washer from muzzle brake must be removed).

If there is any gap DO NOT fire the host with the silencer attached. Poor accuracy and product damage may result if the silencer is not seated against thread shoulder.

Silencers must be free of obstructions such as mud, dirt, etc. DO NOT attempt to shoot through an obstructed silencer.

The silencer is designed to suppress the initial muzzle blast and subsequent projectile de-corking pressure. The silencer doesn't contact or otherwise interact with the bullet, allowing the projectile to travel at its default speed.

A sonic crack may be produced by the projectile as it breaks the sound barrier. This is solely a function of the projectile breaking the sound barrier and is not related to product performance.

To ensure your silencer remains secure while firing, it is of the utmost importance that you frequently verify the silencer is securely tightened onto the barrel. We recommend checking the security of the attachment after 30 discharges of the firearm.

Before removing the silencer from the host firearm, be sure that the firearm is unloaded and the action is opened so that it is visibly clear of any ammunition. When removing the silencer, use extreme caution as it may be hot to the touch after firing. Use a Devour™ suppressor cover (sold separately) or gloves to avoid burns or other injuries.

Once the silencer is removed from the host firearm, BANISH recommends using a thread protector or other muzzle device to protect the muzzle threads and crown during storage or transport.

Introducing the Banish 30-GOLD-V2. This quick-detach, 30 caliber suppressor is the most versatile in the Banish line. It is rated for rimfire to .300RUM. While all Banish™ suppressors have been designed for unmatched sound suppression, testing shows that the Banish 30-GOLD-V2 reduces report down to a whopping 129 decibels on a .308!

The new Banish 30-GOLD-V2 brings a user-serviceable design that is lighter weight and shorter, as well as quieter than anything we've ever tested. Like all Banish suppressors, the Banish 30-GOLD-V2 is made from an ultra-strong, titanium alloy, for unmatched durability. You won't find a lighter and quieter "can" anywhere!

The Banish 30-GOLD-V2 comes as an 8.2-inch quick-detach suppressor holding eleven STifle™ baffles. It comes with a 5/8x24 muzzle break and shim kit for timing your brake.

Perfect for the range, hunting or any other shooting application, the Banish 30-GOLD-V2 will significantly reduce the report and recoil of large-caliber rifles, while still being effective on rifles down to rimfire calibers.



SPECS

LENGTH: 8.2" | **DIAMETER:** 1.593" | **NUMBER OF BAFFLES:** 11 | **WEIGHT:** 13.2oz
MATERIAL: TITANIUM | **THREAD PITCH:** Comes standard with 5/8x24 Muzzle Brake
SELF-SERVICE: YES | **CALIBER:** .308/7.62 | **CALIBER RANGE:** .17 to .300RUM
COLOR: BLACK | **FINISH:** CERAKOTE | **FULL-AUTO RATED:** FULL-AUTO RATED
MOUNT STYLE: HUB MOUNT | **SOUND REDUCTION:** 36db | **LIFETIME WARRANTY:** YES

INSTALLATION OF MUZZLE BRAKE AND SUPPRESSOR

Always ensure the firearm is unloaded when attaching or removing a muzzle brake or a suppressor. After confirming that your firearm is unloaded, remove any preceding muzzle device and crush washer.

Watch our online tutorial on how to install a muzzle brake and shim kit at www.YouTube.com/SilencerCentral. Items included are: 5/8x24 Muzzle Brake (MB), and Muzzle Brake insert. You will also need to use Red Loctite/ Rocksett (not included).

1. Make sure to clean the threads of your barrel prior to installation of muzzle brake.
2. Attach the new muzzle brake onto the barrel all the way by hand without using shims until it shoulders tight to the barrel.
3. Unscrew the MB so that the center point (engraved BANISH) is perpendicular to the plane of the barrel in the 12 o'clock position. The 12 o'clock position will be the final orientation of the MB with BANISH logo facing directly upward. (See figure 1) *When you back the muzzle brake off the shoulder, it will NOT be a full 360 degree rotation.
4. Once you have placed the brake at the 12 o'clock position, unscrew one additional quarter turn to the 9 o'clock position. This will allow for tightening the MB into the correct position.
5. The space between the brake and the shoulder of the barrel located at the rear of the threads will be where the shims will sit. Select the shims with varying thickness that will fit snuggly in this space. This will be different on every firearm and may require some slight trial and error. Use as few shims as possible to fill the void is the best practice. Start with the thickest shim and find the best combination that allows for the tightest fit within the space between the MB and barrel shoulder. Save excess shims for later use.
6. Once you have found the combination resulting in the tightest fit, remove the brake completely from the barrel and place that combination of shims over the threads of the barrel to the shoulder. Then screw on the brake to the threads of the barrel by hand. If this process has been completed correctly, the brake should return to the BANISH logo returning to the 9 o'clock position.
7. Using a crescent wrench or $\frac{3}{4}$ " wrench tighten the muzzle brake $\frac{1}{4}$ turn to allow for the muzzle brake to sit at the 12 o'clock position.
8. Once the practice timing is perfect in the 12 o'clock position, remove the muzzle brake completely from the barrel and apply Red Loctite or Rocksett. Once applied, repeat steps 6 & 7 to set the muzzle brake in place.
9. You are ready to install your BANISH 30-GOLD-V2 Suppressor. Line up your BANISH 30-GOLD-V2 suppressor with your muzzle brake and screw on until hand-tight. Ensure the HUB mount muzzle brake insert is threaded into the can prior to installing onto the muzzle brake/firearm.



DISASSEMBLY AND CLEANING

It is recommended that the suppressor be cleaned every 50 - 100 rounds fired. The use of solid lead or plated lead bullets is not recommended.

To disassemble, make sure the firearm is unloaded and unscrew to remove from host firearm.

Using the provided tool key and T-45 torx wrench, remove the end cap of the suppressor. For best results, we recommend permanently attaching the T-45 torx wrench and the tool key together. This can be done with "JB Weld" or similar product found at any local hardware store.

Using your solvent of choice, spray the inside of the suppressor and let sit for 24 hours.

Push baffles out of the tube with our Baffle Removal Tool (sold separately) or a wooden dowel.

The suppressor has 10 indexed baffles and one accuracy baffle (indicated by the four holes and no center cut). Care must be taken when reassembling.

Use a stiff bristle brush (brass or nylon) with solvent / carbon killer of choice to clean the baffles and inside the tube.

Make sure all parts are clean and solvent has been removed.



ASSEMBLY


Using a flat surface, stack the 10 indexed baffles on top of each other, then place the accuracy baffle on top. Make sure the indexing tabs are aligned and fully engaged in each corresponding baffles.

Slide the tube over the baffle stack. Keeping the tube in the upright position, with one hand, slide the centerline of the tube to the edge of the table. While holding the tube with one hand, use one finger on the other hand to push the baffles up the tube.


Flip the assembly over so the open end is up. Apply anti-sieze to the threads before installing the end cap.

Care must be taken during assembly to ensure the indexing tab on the baffles are aligned with each corresponding baffle before tightening end cap.


Lightly tighten the end cap, when the baffles are properly aligned only the edge of the end cap will be exposed (approximately 1/32"). If more than 1/32" is exposed the tabs on the baffles are not properly aligned. Finish tightening end cap to 110 - 120 inch pounds.



Indexed baffles (10) with center cut must be fit together.



Accuracy baffle (1) with four holes around and no center cut.





BANISH

LIFETIME WARRANTY

We provide a lifetime warranty against all manufacturing defects and damages caused by the normal use of our products. We will repair or replace free of charge any suppressor manufactured by, or at the direction of, BANISH Suppressors. The product is sold "as is" with no further implied contractual rights or warranties beyond those expressly stated herein.

The lifetime warranty does not apply to certain conditions or acts. It is at the sole discretion and determination of BANISH Suppressors if a defect or condition is covered by this warranty. Conditions not covered include, but are not limited to: modifications, abuse, neglect, use of defective ammunition, use of improperly sized ammunition, and criminal conduct. BANISH Suppressors assumes no liability for damages or bodily injury caused by such acts or omissions as previously described. Abuse and neglect are defined as usage outside of the reasonable scope for which the product is intended, thus contributing to the accelerated and unreasonable premature wear of the suppressor itself.

If a repair is required, the owner must contact our Customer Service Department. Our customer service representative will arrange for return of the suppressor at manufacturer's shipping expense. PLEASE DO NOT SHIP THE SUPPRESSOR FOR REPAIR WITHOUT FIRST CONTACTING CUSTOMER SERVICE AND DO NOT SHIP IN ANY EVENT WITHOUT A COPY OF THE APPROVED BATFE FORM.

When you ship the suppressor back to the manufacturer, please include a detailed statement concerning

the type of defect or malfunction encountered, describe the ammunition used and type of host weapon the product was used on or attached to.

If for any reason your suppressor is not eligible for repair or replacement, you may purchase a replacement suppressor for 50% off the MSRP for a same or similar suppressor.

Please contact our Customer Service Department at 888-781-8778 for further details and requirements.

RETURN SHIPPING

The cost of shipping for any items returned to Silencer Central is the responsibility of the customer, with the exception of warranty claim returns. Return shipping to Silencer Central for warranty claims and/or repairs are covered by Silencer Central as long as Customer Service is contacted in advance and a warranty claim form is completed by the customer.