



# BANISH

 [banishsuppressors.com](http://banishsuppressors.com)

 877.904.5292

 [info@banishsuppressors.com](mailto:info@banishsuppressors.com)

# BANISH 9

## OWNER'S MANUAL



BANISH Suppressors has always had one overriding goal in mind - to make the most user-friendly suppressor on the market. And what is more user-friendly than being multi-caliber? At BANISH Suppressors, we are proud of what we've accomplished, and we want to share with you what makes a BANISH Suppressor stand out from the crowd.

Our unique WhisperTech™ tube is where the BANISH multi-caliber system starts, with a lightweight titanium alloy tube. BANISH Suppressors are light-weight and tough enough for a lifetime of service. The internal baffles handle the gas in such a way that the suppressor significantly reduces recoil as well as sound.



# WARNING

---

To provide for your safety and the effective use of this silencer, it is important that the owner and any user of the silencer read this entire manual and strictly follow the warnings and instructions within. This silencer should be used only by those who are well-versed in the safe operation of firearms.

Failure to follow installation and maintenance instructions in this manual may result in serious personal injury and damage to the firearm.

Suppressed firearms make less noise than unsuppressed firearms and it is easy to forget that they are still capable of causing bodily injury and property damage. Remember, a suppressed firearm should be treated with the same safety and caution as an unsuppressed firearm. Before installing the silencer, be sure that the firearm is unloaded and the action is opened and visibly clear of any ammunition. If you are at all unsure as to the proper procedures to ensure that your firearm is unloaded, please consult your firearm user's manual/instructions and/or contact a properly licensed dealer or the manufacturer of your firearm.

Firearm silencers are user-attached firearm muzzle devices, and as such are subject to improper attachment issues unless the procedures outlined in this manual are followed precisely.

Check the fit between your barrel and silencer before firing! The thread mount must be fully shouldered on the barrel. For direct thread silencers, there should be no visible gap between the barrel shoulder and the face of the silencer thread mount (crush washer from muzzle brake must be removed).

For quick detach suppressors, the muzzle brake must be seated to the shoulder of the firearm and timed properly using the shim kits provided.

If there is any gap DO NOT fire the host with the silencer attached. Poor accuracy and product damage may result if the silencer is not seated against thread shoulder.

Silencers must be free of obstructions such as mud, dirt, etc. DO NOT attempt to shoot through an obstructed silencer.

The silencer is designed to suppress the initial muzzle blast and subsequent projectile de-corking pressure. The silencer doesn't contact or otherwise interact with the bullet, allowing the projectile to travel at its default speed.

A sonic crack may be produced by the projectile as it breaks the sound barrier. This is solely a function of the projectile breaking the sound barrier and is not related to product performance.

To ensure your silencer remains secure while firing, it is of the utmost importance that you frequently verify the silencer is securely tightened onto the barrel. We recommend checking the security of the attachment after 5 discharges of the firearm and every 30 discharges thereafter.

Before removing the silencer from the host firearm, be sure that the firearm is unloaded, and the action is opened so that it is visibly clear of any ammunition. When removing the silencer, use extreme caution as it may be hot to the touch after firing. Use a suppressor cover (sold separately) or gloves to avoid burns or other injuries.

Once the silencer is removed from the host firearm, BANISH recommends using a thread protector or other muzzle device to protect the muzzle threads and crown during storage or transport.

The engineers at BANISH had two goals for a new suppressor – Make it for the 9mm cartridge and make it quiet. The result is the BANISH 9, a compact and lightweight, full-size 9mm silencer that is one of, if not the quietest 9mm suppressors on the market today. It will work on pistols and pistol-caliber carbines, as well as some full-sized rifles, that the suppressor is rated for. It works for cartridges between .380 and 9mm, including .300 BLK and 350 Legend.

As if the light and quiet suppressor wasn't enough, the engineers developed something totally new and exclusive to BANISH – The Micro Booster. The Micro Booster helps the pistol cycle smoothly and is the smallest and lightest booster anywhere. It comes with the BANISH 9 and is threaded 1/2×28. Additional piston sizes including M13.5×1L and 5/8×24 as well as all three sizes of DT mounts available for separate purchase.

The BANISH 9 measures 6.8 inches long (7.16 inches with the Micro Booster installed). It weighs just 6.73 ounces, and the Micro Booster only adds 1.84 ounces to the weight. It is made using 7075 aluminum for the main tube and front cap, and titanium for the 14 baffles. It is full-auto rated for 9mm supersonic and .300 BLK subsonic. Looking for the quietest 9mm can? You've found it in the BANISH 9.



## SPECS

**LENGTH:** 6.8" without or 7.16" with Micro Booster | **DIAMETER:** 1.35" | **COLOR:** BLACK

**WEIGHT:** 6.7 oz without or 8.6 oz with Micro Booster

**MATERIAL:** TITANIUM Construction with 7075 ALUMINUM Main Tube and Front Cap

**NUMBER OF BAFFLES:** 14 | **THREAD PITCH:** 1/2X28, 5/8×24, M13.5×1LH | **FINISH:** ANODIZE AND CERAKOTE

**CALIBER:** 9mm | **CALIBER RANGE:** .380, 5.7×28, 9mm, .300 BLK, 350 Legend

**FULLY AUTO RATED:** FULL AUTO RATED FOR SUPERSONIC 9mm AND SUBSONIC 300 BLACKOUT

**MOUNT STYLE:** 1/2×28 Micro Booster (comes standard). Additional Piston and Direct Thread Mounts Available

**SOUND REDUCTION:** Up to 34db | **LIFETIME WARRANTY:** YES | **SELF-SERVICE:** YES

# INSTALLATION OF SUPPRESSOR

Always ensure the firearm is unloaded when attaching or removing suppressor. After confirming that your firearm is unloaded, place the threaded end of the BANISH 9 in line with the threads of the barrel.

Ensure the threads on the barrel and suppressor are clean and undamaged, screw the suppressor onto the barrel threads until the suppressor firmly seats against shoulder.

Take special care to avoid cross-threading as damage to the suppressor and barrel threads will result, as well as misalignment of the suppressor with the bore of the firearm.

This may result in a potential baffle strike that could cause serious personal injury and damage to both the firearm and suppressor. Since direct thread mounted suppressors can loosen or unscrew during firing, it is extremely important that the operator frequently checks that the silencer remains securely threaded to the barrel.

Please note, the suppressor will be very hot during and after firing. Wait until the suppressor cools or use a Silencer Central™ suppressor cover to retighten.

Hand tighten suppressor only. Ready for use.

# INSTALLATION OF MICRO BOOSTER INTO SUPPRESSOR

Always ensure the firearm is unloaded when attaching or removing suppressor. After confirming that your firearm is unloaded, place the threaded end of the BANISH 9 in line with the threads of the barrel.

Ensure the threads on the barrel and suppressor are clean and undamaged, screw the Micro Booster onto the barrel threads until the suppressor firmly seats against shoulder.

Take special care to avoid cross-threading as damage to the suppressor and barrel threads will result, as well as misalignment of the suppressor with the bore of the firearm.

Install the o-ring into the inner diameter groove of the piston housing. Place the spring over the barrel of the piston and slide both parts into the piston housing. place the spring retainer over the back end of the piston, inside of the piston housing. Using a snap ring pliers install the C-Clip behind the piston/spring retainer locking it into the groove on the bottom side of the piston housing.

Ensure micro booster assembly is securely threaded into and tightened into the suppressor. Check frequently that the mount is securely installed into the suppressor and remains securely threaded to the barrel.

Please note, the suppressor will be very hot during and after firing. Wait until the suppressor cools or use a Silencer Central™ suppressor cover to retighten.

Hand tighten suppressor only. Ready for use.





# ASSEMBLY – SUPPRESSOR

Using a flat surface, stack 13 index baffles on top of each other. Make sure the indexing tabs are aligned and fully engaged in each corresponding baffle. Place blast baffle on top of baffle stack (this baffle does not have index tabs on the top/cone end of it.)

Slide the tube over the baffle stack. Keeping the tube in the upright position, with one hand, slide the centerline of the tube to the edge of the table. While holding the tube with one hand, use one finger on the other hand to push the baffles up the tube.

Flip the assembly over so the open end is up. Apply anti-sieze to the threads before installing the end cap.

Install the end cap and hand tighten.





# BANISH

## CLEANING & DISASSEMBLY

It is recommended that the suppressor be cleaned every 50 - 100 rounds fired. The use of solid lead or plated lead bullets is not recommended.

To disassemble make sure the firearm is unloaded and remove from host firearm.

Using the provided tool key and T-45 torx wrench, remove the end cap of the suppressor.

Remove the front module from the main tube.

The end cap of the suppressor that threads onto the barrel is not intended to be removed from the main tube of the suppressor.

Using your solvent of choice, spray the inside of the suppressor and let sit for 24 hours.

Push baffles out of the tube with our Baffle Removal Tool (sold separately) or a wooden dowel.

The suppressor is 6.8" or 7.16" with or without the Micro Booster as well as having 14 baffles. Care must be taken when reassembling.

Use a stiff bristle brush (brass or nylon) with solvent / carbon killer of choice to clean the baffles and inside the tube.

Make sure all parts are clean and solvent has been removed.





# BANISH

## LIFETIME WARRANTY

We provide a lifetime warranty against all manufacturing defects and damages caused by the normal use of our products. We will repair or replace free of charge any suppressor manufactured by, or at the direction of, BANISH Suppressors. The product is sold "as is" with no further implied contractual rights or warranties beyond those expressly stated herein.

The lifetime warranty does not apply to certain conditions or acts. It is at the sole discretion and determination of BANISH Suppressors if a defect or condition is covered by this warranty. Conditions not covered include, but are not limited to: modifications, abuse, neglect, use of defective ammunition, use of improperly sized ammunition, and criminal conduct. BANISH Suppressors assumes no liability for damages or bodily injury caused by such acts or omissions as previously described. Abuse and neglect are defined as usage outside of the reasonable scope for which the product is intended, thus contributing to the accelerated and unreasonable premature wear of the suppressor itself.

If a repair is required, the owner must contact our Customer Service Department. Our customer service representative will arrange for return of the suppressor at manufacturer's shipping expense. PLEASE DO NOT SHIP THE SUPPRESSOR FOR REPAIR WITHOUT FIRST CONTACTING CUSTOMER SERVICE AND DO NOT SHIP IN ANY EVENT WITHOUT A COPY OF THE APPROVED BATFE FORM.

When you ship the suppressor back to the manufacturer, please include a detailed statement concerning the type of defect or malfunction encountered, describe the ammunition used and type of host weapon the product was used on or attached to.

If for any reason your suppressor is not eligible for repair or replacement, you may purchase a replacement suppressor for 50% off the MSRP for a same or similar suppressor.

Please contact our Customer Service Department at 888-781-8778 for further details and requirements.

### RETURN SHIPPING

The cost of shipping for any items returned to Silencer Central is the responsibility of the customer, with the exception of warranty claim returns. Return shipping to Silencer Central for warranty claims and/or repairs are covered by Silencer Central as long as Customer Service is contacted in advance and a warranty claim form is completed by the customer.