


HURST The Solid Fuel People

- (1) Hybrid" Firetube/Watertube Vessel Design
- (2) Watertube Section
- (3) Firetube Section
- (4) Reciprocating Fire Grates
- (5) Under Fire Air Fan
- (6) Reciprocating Drive
- (7) Over Fire Fan/Dampers
- (8) Carry-Over Reinjection Blower
- (9) Fire Door
- (10) Ash Clean Out Door
- (11) Optional Back Up Burner
- (12) Fuel Metering Bin
- (13) Ash Removal Conveyor
- (14) Refractory Arch

The Hybrid RG design is suitable for applications to produce high pressure steam or hot water in ranges from 3,450 - 60,000 lbs/hr (3.4 mmBTU – 60 mmBTU) output from 100 up to 400 PSI. This system is designed by HBC to combine the best technologies from the "old school" of biomass combustion and the latest advanced combustion control technologies. The new HBC reciprocating grate-type stoker system permits biomass fuels with a high proportion of incombustibles to be combusted in an efficient manner with the added advantage of automatic de-ashing. This combination is particularly suitable for heating applications in lumber dry kilns, veneer log vats, veneer dryers, greenhouses, factories, schools and office buildings. This combination enables these systems to provide a flexible and reliable operation utilizing a consistent "grade" of biomass waste with moisture contents ranging from 30 - 50%. The boiler vessel is a two pass hybrid design incorporating a water tubed boiler-type water membrane and a two-pass fire tube scotch marine vessel. This vessel's advantages over standard water tube boilers include much larger steam disengagement area providing high quality steam, larger steam storage capability for quicker response to sudden steam demand and much larger thermal storage that provides fast demand response times and safer operation.

HURST BOILER & WELDING CO., INC. P. O. Drawer 530 21971 Highway 319 N. Coolidge, Georgia 31738 Toll Free: 1-877-994-8778 Tel: (229) 346-3545 Fax.(229) 346-3874 Email: info@hurstboiler.com



CAT # W-02



Reciprocating Grate System

