

ALTV2416CBI220

CCTV Power Supply, 16 Isolated PTC Class 2 Outputs, 24VAC
@ 25A, 220VAC, BC300 Enclosure

ALTV2416CBI220 Isolated CCTV Power Supplies provide 24VAC distributed via sixteen (16) PTC protected isolated outputs for powering CCTV Cameras, heaters and other video accessories.



Specifications

Input

- 220VAC, 50/60Hz, 5.4A.

Output

- Sixteen (16) PTC protected outputs (auto-resettable).
- 24VAC @ 28A (672VA) supply current.
- Outputs are rated @ 2.5A.
- Surge suppression.

Electrical

Temperature:

- Operating: 0° C to 49° C (32° F to 120° F).
- Storage: - 20° C to 70° C (- 4° F to 158° F).
- Relative Humidity 85% +/- 5%.
- BTU/Hr (approx.): 344 BTU/Hr.
- System AC input VA requirement: 1188VA.

Features

- Illuminated master power disconnect circuit breaker with manual reset.
- Spare fuses provided.
- Unit maintains camera synchronization.

Agency Listings

CE Compliant

Dimensions & Weight

Enclosure:

Wall mount enclosure for indoor use.

Dimensions 13"W x 13.5"H x 3.25"D (330 mm W x 343 mm H x 83 mm D).

1/2" and 3/4" combination knockouts.

Weights (approximate):

Product Weight: 23.3 Lbs. (10.57 kg).

Shipping Weight: 24.3 Lbs. (11.02 kg).