



IR151B Single-Bed & IR152B Double Bed Patient Stations



FEATURES

- Call reset push button
- Intercom indicator lights when room is monitored
- Push button calling from call cord(s)
- Call-placed LED indicator(s)
- Sensitive speaker/microphone

ARCHITECTS' & ENGINEERS' SPECIFICATIONS

Patient Station(s) shall be Alpha Communications®/Tektone **IR151B** and/or **IR152B**, or approved equal. Model **IR151B** shall contain call-placed and intercom in-use indicators, cancel button, call cord jack and a 2.50" speaker/microphone with voice response. Model **IR152B** shall include all of above with an additional call cord jack and call-placed indicator.

Removal of a cord, either accidentally or intentionally, will place a call, which can be canceled only by replacing the cord or its equivalent into the call jack. All station components shall be mounted on an attractive flame retardant ABS plastic faceplate, in fog white color. Connections shall be plug-in type. The station(s) shall be use a 2.50" x 2.50" speaker/microphone for accurate voice reproduction.

Contractor shall observe all local and national electrical and building codes.

The **IR151B** and **IR152B** station(s) shall be UL 1069 listed to the latest 4th Edition Standards

IR151B SINGLE BED PATIENT STATION

The Alpha Communications® **IR151B** Patient Station provides for efficient use of the nursing staff by permitting fast and reliable audio communication between nurse and patient.

Calling the nurse is accomplished by pressing the call button on the end of the 8 to 10 foot long call cord. A non-resettable call is registered if the call cord is accidentally removed from its jack. Callplaced assurance and intercom operation is indicated by reliable solid state LED indicator lamps.

The speaker/microphone is sensitive enough to assure clear conversations even with weak patients. A call reset button is also provided on the rugged ABS plastic faceplate.

IR152B DUAL BED PATIENT STATION

The **IR152B** has the same specifications and features as the **IR151B** except that it includes two call cord jacks and two call-placed indicators for use with two patient beds (in close proximity to each other).



SPECIFICATIONS

Dimensions:	Height: 4.50" (119mm) Width: 6.38" (162mm) Depth: 2.75" (70mm) Projects: 0.50" (12.7mm)
Construction:	Attractive, flame retardant type ABS Plastic Faceplate
Connections:	Plug-in type
Finish:	Light texture, fog white
Speaker:	2.50" x 2.50", 60 ohm with voice response
Housing:	Alpha Communications® IH353 Box with IH352 Ring or Steel City #H3BD with #3GC plaster ring, or EXACT equal. Horizontal mount.

SF301/8 OR SF301/10 CALL CORD SWITCH

Use **SF301/8** (8 foot) or **SF301/10** (10 foot) call cord, or other specialty type (i.e. Geriatric type). Includes **HW155** pillow/bedsheet clip.



Cord Construction: One piece molded, 8' or 10' long

Push Button: Momentary contact

Alpha Communications

42 Central Drive • Farmingdale • NY • 11735-1202 • Phone: (631) 777-5500 • Fax: (631) 777-5599
TOLL-FREE: (800) 666-4800 • Web: www.alphacommunications.com • Email: info@alphacommunications.com

Copyright© 1998-2023 Alpha Communications® - All Rights Reserved.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.