

**3061S****SLAVE BUTTON WITH NAMEPLATE**

Slave button that can be used in both 2-wire and ViP digital systems, consisting of a nameplate and a steel pressure call button. The brightness of the white LED is adjustable on the back. The installation is foreseen on 2.5 mm thick metal plates.


3061S

SLAVE BUTTON WITH NAMEPLATE

GENERAL DATA

Height (inch) (in)	0.98
Width (inch) (in)	3.54
Depth (inch) (in)	0.98
Flush-mounted	Yes

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888CU	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes
ViP	Yes

ELECTRICAL CHARACTERISTICS

Absorption in stand-by (W)	0
Maximum absorption (W)	0.06

HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Backlight color	White

SETTINGS

Backlight brightness	Yes
----------------------	-----

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°F)	-13 ÷ 131
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV



3061S

SLAVE BUTTON WITH NAMEPLATE

ENVIRONMENTAL AND COMPLIANCE FEATURES

Certifications

EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)