



3360B

2-WIRE AND VIP CALL MODULE. IKALL SERIES



Digital call module with 128x64 dot graphic LCD display and keypad with 21 buttons backlit with blue LEDs. Also functions as an electronic key code. Two search buttons are used to scroll through the names; alternatively, the first letter of the required name can be entered. Once the desired username is displayed, simply press the call button. The call can also be made by directly entering the user code. It can also be used to customise an initial welcome message and can operate with a dual user interface language. It can be used in conjunction with Simplekey electronic keys for automatic updating of names in the directory. For the SBC system (factory setting), the electronic name directory saves up to 3500 user names and 6000 lock-release passwords. Users and settings are simple to program using PC software art. 1249B (included, with USB connection cable) via a USB or RS485 port, or locally on the digital module itself. Includes the CD-ROM loaded with serial download SW art. 1249B for installation to PC and the USB connection cable. Dimensions: 112x180x40



3360B

2-WIRE AND VIP CALL MODULE. IKALL SERIES

GENERAL DATA

Height (inch) (in)	7.09
Width (inch) (in)	4.41
Depth (inch) (in)	1.57
Product color	Black RAL9005
Flush-mounted	Yes
Wall-mounted	Yes

DISPLAY

Display size (")	3
------------------	---

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°F)	-13 ÷ 131
Operating humidity (RH max) (%)	25 ÷ 75

MAIN FUNCTIONS

No. of storable users (n°)	3500
----------------------------	------

GENERAL FEATURES

Key button function	Yes
---------------------	-----