

**VS8111****VISTO WI-FI EXTERNAL UNIT. VIP SYSTEM**

Wi-Fi video entry external unit for use in Comelit ViP systems, complete with adapter allowing use of the power supply for the existing bell (12-20 VAC or 12-33 VDC) and allowing interfacing with the existing bell. Depending on the system configuration, you can receive video entry phone calls on ViP monitors or directly on smartphones and tablets via the Comelit app. With the Comelit app, you are always in touch with what is going on at your home, whether you are in town or even in another country.



VS8111

VISTO WI-FI EXTERNAL UNIT. VIP SYSTEM

GENERAL DATA

Type	Monoblock
Height (mm)	136
Width (mm)	47
Depth (mm)	32
Product color	Dark Graphite RAL9011
Wall-mounted	Yes

COMPATIBLE SYSTEMS

ViP	Yes
-----	-----

AUDIO FEATURES

Technologies implemented	Full-Duplex, Echo canceling, Noise reduction
--------------------------	--

CAMERA FEATURES

Camera	Colours
Sensor type	1/4" CMOS
Lens optical dimensions (mm)	1.6
Angle of view (H x V - °)	170 (diagonal)
Sensitivity	2
Video compression	H.264

ELECTRICAL CHARACTERISTICS

Type of power supply	External power supply
Supply voltage	12÷33 VDC
Maximum absorption (W)	6

HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	1



VS8111

VISTO WI-FI EXTERNAL UNIT. VIP SYSTEM

HARDWARE FEATURES

Clamps	+ - NO C
Removable terminals	Yes
Number of outputs (n°)	1
Type of outputs	Relay (C-NO, 1A@30VDC)

NETWORK AND COMMUNICATION PROTOCOLS

Type of Wi-Fi connection	2.4 GHz
IP address assignment	DHCP, AUTO IP, static IP

PROGRAMMING MODE

ViP Manager software	Yes
----------------------	-----

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP54
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	0 ÷ 75
Environmental class	III
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), RED 2014/53/UE (EN 62311:2008, EN 62368-1:2014, EN 61000-6-1:2007, EN 61000-6-3:2007 + A1:2011, ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300 328 V2.1.1)

MAIN FUNCTIONS

Visual indications of system status	Yes
-------------------------------------	-----



VS8111

VISTO WI-FI EXTERNAL UNIT. VIP SYSTEM

ACCESSORIES



3534

24VDC POWER SUPPLY UNIT WITH EU-UK-US PLUG

Power supply for Visto smart doorbell, input voltage 110÷240 VAC, output voltage 24 VDC. Interchangeable plugs for the European, English and American markets supplied.



3528

ADAPTER PLATE FOR VISTO KIT

Plate for the installation of the Visto smart doorbell on existing recessed boxes type 503 (horizontal and vertical) with interaxis of 83.5mm, square boxes with interaxis of 62mm, box type 502/German/round with interaxis of 60mm. Made of PMMA, white color.



3526

UP-DOWN ADJUSTABLE BRACKET FOR VISTO

Up/down adjustable bracket for Visto smart doorbell, 10° vertical inclination, plastic material, silver mist RAL9006 colour.



3532

ADDITIONAL WIRELESS BELL FOR VISTO KIT

Wireless additional bell for Visto smart doorbell, 433 MHz operating frequency, adjustable volume, various selectable melodies, powered by 2 batteries (size AA, 1.5V, not included), wall mounting, white/silver color.



3527W

CLOUD WHITE COVER FOR VISTO EXTERNAL UNIT

Cover replacement for Visto smart doorbell. Plastic material, cloud white RAL9003 color.

**VS8111****VISTO WI-FI EXTERNAL UNIT. VIP SYSTEM****ACCESSORIES****3527S****SILVER MIST COVER FOR VISTO EXTERNAL UNIT**

Cover replacement for Visto smart doorbell. Plastic material, silver mist RAL9006 color.

**3527B****DARK GRAPHITE COVER FOR VISTO EXTERNAL UNIT**

Cover replacement for Visto smart doorbell. Plastic material, dark graphite RAL9011 color.

**3525****LEFT-RIGHT ADJUSTABLE BRACKET FOR VISTO**

Left/right adjustable bracket for Visto smart doorbell, 20° horizontal inclination, plastic material, silver mist RAL9006 colour.

**3522****ADAPTER FOR WI-FI VISTO KIT**

Voltage adapter for Visto smart doorbell. Input voltage 12÷20 VAC, output for powering the Visto smart doorbell. It is possible to control already existing bells. Case in plastic material, dark graphite RAL9011 color. Dimensions (W x H x D): 59 x 40 x 14mm.

**CONAL02A****Power supply connector w/ female terminals/jack**

Connector for power supply, 2 screw terminals, female jack type connector.