



# 5819S

## Wireless Combination Magnetic Contact and Shock Sensor

### Two Types of Protection in One Product.

The 5819S wireless combination magnetic contact and shock sensor provides two types of protection in one product and offers more protection at every point. As a standard magnetic contact, it can detect open and closed conditions of doors and windows. It also has built in shock sensing technology that can detect abrupt, forcible attempts at entry.

### Flexibility and Design.

The combination zone feature allows an installer to set the contact and shock conditions as independent alarm signals, or to flip a switch to combine them into one for larger systems with many points of protection. At 40% smaller than the previous model, the 5819S in white or brown blends easily with any décor.

### Easy to Install.

Installation and set-up is simplified because of four basic sensitivity settings, an omni-directional shock sensor for maximum mounting flexibility, and LED feedback when adjusting the shock sensor.



*Small, powerful, white or brown, and with multiple mounting options and four simple sensitivity settings, the 5819S is the ultimate in design, easy installation and flexibility.*

## FEATURES AND BENEFITS

### Two In One

All-in-one door and window shock sensor

### Design

40% smaller than the previous model and available in white or brown.

### Easy To Install

Four simple settings and LED indicator during setup.

### Flexibility

Omnidirectional shock sensor for maximum installation flexibility.

### When You Need More

Auxillary terminals for a third protection point if needed.

# 5819S Technical Specifications

## ELECTRICAL SPECIFICATIONS

**Voltage:** 3 volts DC

**Number of Batteries:** 1

**Battery Type:** CR-123 lithium

**Battery Manufacturer:** Duracell® or Panasonic™ only

**Includes:** Auxillary terminals

## PHYSICAL SPECIFICATIONS

**Diameter:** 1.19"

**Height:** 3.06"

**Width:** 1.56"

**Weight:** 0.1 lbs without battery; entire package 0.19 lbs

**Operating Temperature Range:** 0 - 49°C (32 - 120°F)

**Storage Temperature Range:** -20 - 60°C (-4 - 140°F)

**Operating Humidity Range:** Up to 95% non-condensing humidity

**Mounting:** Adhesive tape and mounting hardware included; Magnet also included.

## LISTINGS/CERTIFICATIONS

5819S is cETLus Listed to UL 639 Standard for Intrusion Detection Units

ULC S306 Intrusion Detection Devices

UL 634 Guide for the Investigation of Connectors and Switches for Use with Burglar Alarm Systems

## ORDERING

5819S	White wireless combination contact and shock sensor for use with the Honeywell Home 5800 Series.
5819S-BR	Brown wireless combination contact and shock sensor for use with the Honeywell Home 5800 Series.

### For more information

[security.honeywellhome.com/hsc](http://security.honeywellhome.com/hsc)



### Resideo Technologies, Inc.

2 Corporate Center Drive, Suite 100

P.O. Box 9040

Melville, NY 11747

1-800-645-7492

[resideo.com](http://resideo.com)

L/5819SD/D | 06/19

© 2019 Resideo Technologies, Inc.

This product is manufactured by Resideo and its affiliates. The Honeywell Home trademark is used under license from Honeywell International Inc. All rights reserved.

**Honeywell Home**