



**NAPCO**

333 Bayview Avenue

Amityville, New York 11701

For Sales and Repairs, (800) 645-9445

For Technical Service, (800) 645-9440 or visit us at

<http://tech.napcosecurity.com/>

(Note: Technical Service is for security professionals only)

Publicly traded on NASDAQ Symbol: NSSC

© NAPCO 2016

## GEMC-PS24V7A-R 7 AMP SUPERVISED POWER SUPPLY / CHARGER DATA SHEET

WI1892A 01/16

### DESCRIPTION

The GEMC-PS24V7A-R is both a charger and a supervised power supply rated at 24VDC/7A. Input rating is 120VAC, 60Hz, 3A. Fuse rated 5A, 250V. Replace only with UL Listed fuse rated 5A, 250V (see WI1653).



### FEATURES

- 24VDC output.
- Maximum charge current 1.96A.
- 7 ampere continuous supply current at 24VDC.
- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.

- AC input, DC output.
- Short circuit and thermal overload protection. Specified at 25°C ambient.

### PHYSICAL

Board Dimensions: 9"(L) x 6"(W) x 1 $\frac{5}{8}$ "(H)

### AGENCY LISTINGS

UL864 9th Edition: Commercial Fire  
UL985 Household Fire Warning System Units  
NFPA 72 National Fire Alarm Code  
CSFM: California State Fire Marshall  
NYCFD: NYC Fire Department

### ORDERING INFORMATION

GEMC-PS24V7A-R: 7A, 24V Power Supply



**NAPCO**

333 Bayview Avenue

Amityville, New York 11701

For Sales and Repairs, (800) 645-9445

For Technical Service, (800) 645-9440 or visit us at

<http://tech.napcosecurity.com/>

(Note: Technical Service is for security professionals only)

Publicly traded on NASDAQ Symbol: NSSC

© NAPCO 2016

## GEMC-PS24V7A-R 7 AMP SUPERVISED POWER SUPPLY / CHARGER DATA SHEET

WI1892A 01/16

### DESCRIPTION

The GEMC-PS24V7A-R is both a charger and a supervised power supply rated at 24VDC/7A. Input rating is 120VAC, 60Hz, 3A. Fuse rated 5A, 250V. Replace only with UL Listed fuse rated 5A, 250V (see WI1653).



### FEATURES

- 24VDC output.
- Maximum charge current 1.96A.
- 7 ampere continuous supply current at 24VDC.
- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.

- AC input, DC output.
- Short circuit and thermal overload protection. Specified at 25°C ambient.

### PHYSICAL

Board Dimensions: 9"(L) x 6"(W) x 1 $\frac{5}{8}$ "(H)

### AGENCY LISTINGS

UL864 9th Edition: Commercial Fire  
UL985 Household Fire Warning System Units  
NFPA 72 National Fire Alarm Code  
CSFM: California State Fire Marshall  
NYCFD: NYC Fire Department

### ORDERING INFORMATION

GEMC-PS24V7A-R: 7A, 24V Power Supply