



Clarity 5E Series II module two jack ports (1 unit), ETL verified to TIA Category 5e component specification. Front-loading and front removable. New universal T568A/B wiring label and tapered wiring towers simplify termination. Center tuned to Clarity 5E patch cords for optimum performance.

## Features & Benefits

Center tuned design: Transparent interface with Clarity 5E cords.

Easy lace IDC housing: Reduces wiring time.

Easy to follow T568A and T568B wiring label: Quick, user-friendly, eliminates confusion.

Rugged Series II footprint: Fits in all Series II faceplates and housings.

Front removable: Less intrusive access for adds, moves, changes.

Icon compatible, Category 5e marking on jack face: Supports 606 designation requirements.

## Specifications

### General Info

|                   |             |                    |                       |
|-------------------|-------------|--------------------|-----------------------|
| Product Line      | Ortronics   | UPC Number         | 662875511267          |
| Country Of Origin | Mexico      | Application Sector | Commercial/Industrial |
| Standard          | UL Standard | Type               | Jack                  |

### Dimensions

|                   |         |                  |        |
|-------------------|---------|------------------|--------|
| Product Width US  | 1.9 in  | Product Depth US | 1.2 in |
| Product Height US | 0.92 in |                  |        |

### Additional Information

|                |     |
|----------------|-----|
| RoHS Compliant | Yes |
|----------------|-----|