ENFORCER®

Wireless

433.32MHz RF Receiver Comparison Chart

		SK-910RD2-4	SK-910RE1-4	SK-910RE2-4
Model				
Channels		2	1	2
Frequency		433.92MHz		
Memory capacity		15 transmitters per channel	16 transmitters per channel	
Operating voltage		10~24 VDC/VAC	12~24 VDC/VAC	
Current draw (max. @12VDC)	**Standby**	16mA	12mA	
	Active	60mA per channel		
Relay contacts	**Number**	2	1	2
	Rating	Form C, 10A@14VDC	Form C, 20A@14VDC or 7A@120VAC	
Output functions		0.5~99 sec timed, 1~99 min timed, toggle, latch, validity (follow)	1/10/30 second timed, Toggle	
Programming convenience		One Pushbutton	Two DIP switches for output mode One push button for learning mode	
LED indicators		2-Digit,7-segment LED display	Dual color LED: Red for power on Blue for CH1 indicator Purple for CH2 indicator	
Extended Range Antenna		Optional, SK-93ERSD		
RF Range	**Standard**	Up to 500ft (150m)		
	Ext range antenna	Up to 800ft (270m)		
Certifications		FCC, CE, IC, RoHS		
Dimensions		$4^{3}/_{16}$"x$2^{3}/_{8}$"x$^{15}/_{16}$" (107x60x23 mm)	$2^{3}/_{8}$"x$2^{3}/_{16}$"x$^{15}/_{16}$" (60x55x23 mm)	
Transmitter compatible		SK-939T2-GNUQ	SK-939T1-GBUQ	SK-939T2-GNUQ
		(will work with all SECO-LARM 433.92MHz transmitters)		
Warranty		3-Years		

SECO-LARM® U.S.A., Inc.
16842 Millikan Avenue, Irvine, CA 92606
Phone: (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326
Website: www.seco-larm.com **Email:** sales@seco-larm.com

Copyright © 2027 SECO-LARM U.S.A, Inc. All rights reserved.
All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.
SECO-LARM® ENFORCER® CRIMEBUSTER® CBA® SLI®

ENFORCER®

Inalámbrico ES

Receptor RF de 433.32MHz Tabla Comparativa

		SK-910RD2-4	SK-910RE1-4	SK-910RE2-4
Modelo				
Canales		2	1	2
Frecuencia		433.92MHz		
Capacidad de memoria		15 transmisores por canal	16 transmisores por canal	
Voltaje de operación		10~24 VCC/VCA	12~24 VCC/VCA	
Consumo de corriente (máx. a 12VCC)	**En espera**	16mA	12mA	
	Activo	60mA por canal		
Contactos de relé	**Cantidad**	2	1	2
	Capacidad nominal	Forma C, 10A@14VCC	Forma C, 20A a 14VCC o 7A a 120VCA	
Funciones de salida		Temporizado, 0,5~99 seg., Temporizado, 1~99 min., Alternado, Enclavado, Validez (seguimiento)	Temporizado: 1/10/30 segundos; alternante	
Facilidad de programación		Un pulsador	Dos interruptores DIP para el modo de salida Un pulsador para el modo de aprendizaje	
Indicadores LED		Pantalla LED de 2 dígitos y 7 segmentos	LED de dos colores: Rojo: encendido Azul: indicador de CH1 Morado: indicador de CH2	
Antena de alcance extendido		Opcional, SK-93ERSD		
Alcance RF	**Estándar**	Hasta 500 pies (150m)		
	Antena de alcance extendido	Hasta 800 pies (270m)		
Certificaciones		FCC, CE, IC, RoHS		
Dimensiones		$4^{3}/_{16}$"x$2^{3}/_{8}$"x$^{15}/_{16}$" (107x60x23 mm)	$2^{3}/_{8}$"x$2^{3}/_{16}$"x$^{15}/_{16}$" (60x55x23 mm)	
Compatible con transmisores		SK-939T2-GNUQ	SK-939T1-GBUQ	SK-939T2-GNUQ
		(Compatible con todos los transmisores SECO-LARM de 433.92 MHz)		
Garantía		3 años		

SECO-LARM® U.S.A., Inc.
16842 Millikan Avenue, Irvine, CA 92606
Phone: (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326
Website: www.seco-larm.com **Email:** sales@seco-larm.com

Copyright © 2027 SECO-LARM U.S.A, Inc. Todos los derechos reservados.
Todas la marcas comerciales son propiedad de SECO-LARM U.S.A., Inc. o sus respectivos propietarios.
La póliza de SECO-LARM es de desarrollo y mejora continua. Por esa razón, SECO-LARM se reserva el derecho de cambiar las especificaciones y los precios sin previo aviso. SECO-LARM tampoco es responsable de errores de impresión.
SECO-LARM® ENFORCER® CRIMEBUSTER® CBA® SLI®