



## V Series

# FE9191-H-V2 (1.18 mm)

12MP Fisheye Panoramic AI  
Camera



## Technical Specifications

System Information	
CPU	Multimedia SoC (System-on-Chip)
Flash	8 GB
RAM	2 GB

  

Camera Specifications	
Image Sensor	1/2.3" Progressive CMOS in 4056x3040
Max. Resolution	2816x2816
Lens Type	Fixed-focal
Focal Length	f = 1.18mm
Aperture	F2.18
Iris Type	Fixed iris
Field of View	180° (Horizontal) 180° (Vertical) 180° (Diagonal)
Shutter Time	1/5 sec. to 1/32,000 sec.
WDR Technology	WDR Pro
Day/Night	Yes
Removable IR-cut filter	Yes
Minimum Illumination	0.1 lux @ F2.18 (Color) <0.005 lux @ F2.18 (B/W)
Pan/Tilt/Zoom Functionalities	ePTZ: 12x digital zoom (12x on IE plug-in)
Storage	Seamless Recording to MicroSD/SDHC/SDXC card (1TB capacity supported) and recording to network-attached storage (NAS)

Built-in Installation Aids	Pixel calculator
----------------------------	------------------

## Video

Compression	H.265, H.264, MJPEG
Maximum Frame Rate	30fps @ 2816x2816 (WDR off) 20fps @ 2816x2816 (WDR on)
Maximum Streams	3 video streams (up to 8 configurable profiles)
S/N Ratio	56.9 dB
Dynamic Range	120 dB
Video Streaming	Adjustable resolution, quality and constant bit rate control, Smart Stream III
Image Settings	<p>General settings video title and time stamp overlay, video orientation (flip, mirror), day/night settings</p> <p>anti-overexposure Image settings white balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve), defog, 3DNR</p> <p>Exposure BLC, exposure control, AE speed adjustment, WDR</p> <p>Privacy mask Scheduled profile settings Pixel calculator</p>
Display Mode	<p>Client Dewarping Ceiling mounted: 1O Fisheye, 1P Panoramic, 2P Two Panoramics, 1R One Region, 4R Four Regions, 1O3R One Fisheye Three Regions, 1O8R One Fisheye Eight Regions Wall mounted: 1O Fisheye, 1P Panoramic, 1R One Region, 4R Four Regions, 1P2R One Panoramic Two Regions, 1P3R One Panoramic Three Regions, 1O3R, One Fisheye Three Regions</p> <p>Local Dewarping Ceiling mounted: 1O Fisheye, 1P Panoramic, 2P Two Panoramics, 1R One Region, 4R Four Regions Wall mounted: 1O Fisheye, 1P Panoramic, 1R One Region, 4R Four Regions</p>

## Audio

Audio Capability	One-way Audio
Compression	G.711, G.726, MPEG-2 AAC-LC
Interface	Built-in microphone
Effective Range	5 meters

## Network

Users	Live viewing for up to 10 clients
Security	Access list, Account block , Audit log, Configurable password strength protection, CSRF protection, Digest authentication, HTTPS , IEEE 802.1x, Secure boot, Session timeout, Signed firmware, Trend Micro IoT Security (Brute force attack event, Cyberattack event, Quarantine event), User access log, User account management
Protocols	802.1X, ARP, Bonjour, CIFS/SMB, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMPv3, IPv4, IPv6, NTP, PPPoE, QoS (CoS/DSCP), RTSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS 1.2, UDP, UPnP
Interface	10 Base-T/100 Base-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
ONVIF	Profile G, S, T, M supported, specification available at <a href="http://www.onvif.org">www.onvif.org</a>

AI Analytics	
Compute Capability	SoC with built-in hardware deep learning accelerator
Vision Object Analytics	<p>Object Detection People, Vehicle (4-wheeled, 2-wheeled), Human / Vehicle Bestshot, Path Extraction</p> <p>Attribute Extraction People (gender, clothing color, bag, hat), Vehicle (bike, bus, car, motorcycle, truck, color)</p> <p>Human face Bestshot, Re-Search Extraction</p>
Application	<p>Deep Learning VCA (Smart Motion Detection, Smart VCA) Smart VCA - Group 1 Smart Motion Detection (Five-window video motion detection, People detection, Vehicle detection, Time filter), Smart VCA (Intrusion detection, Loitering detection, Line crossing detection)</p> <p>Smart VCA - Group 2 Unattended object detection, Missing object detection, Crowd detection</p>
Application available with license	<p>Smart VCA - Group 3 Running detection, Parking Violation Detection, Restricted Zone Detection</p> <p>*Support for more analytic applications and free trial, please visit VIVOTEK website.</p>

Solution Integration	
VADP Package	Trend Micro IoT Security (3-year free trial)

Alarm and Event	
Event Trigger	Audio detection, camera tampering detection, cybersecurity events (brute force attack event, cyberattack event, quarantine event), manual trigger, motion detection, periodical trigger, recording notification, SD card life expectancy, shock detection, system boot
Event Action	Event notification via audio clip*, email, HTTP, FTP, NAS server, SD card File upload via email, HTTP, FTP, NAS server, SD card

General	
Connectors	<p>RJ-45 cable connector for 10/100 Mbps PoE network connection</p> <p>Audio input*</p> <p>Audio output*</p> <p>DC 12V power input*</p> <p>Digital input*</p> <p>Digital output* (DO+: 12V, 50mA; DO-: 30V, Open Drain, 1A)</p> <p>* Requires optional cable</p>
LED Indicator	System power and status indicator
Power Input	IEEE 802.3af PoE Class 0
Power Consumption	Max. 9.12 W
Dimensions	ø 150 x 68.4 mm
Weight	701 g

Certifications	<p>EMC  CE (EN 55032 Class B, EN 55035), FCC (FCC Part 15 Subpart B Class B), RCM (AS/NZS CISPR32 Class B), VCCI (VCCI-CISPR 32 Class B), UKCA (BS EN 55032:2015+A11: 2020, BS EN 55035:2017+A11:2020, BS EN IEC 62368-1:2020+A11:2020), ICES-003 Issue 7  BSMI (EMC: CNS 13438, Safety: CNS 14336-1)  Safety:  UL (UL62368-1)  CB (IEC/EN 62368-1, IEC/EN 60950-22, IEC/EN 62471)</p> <p>IA  BIS (IS 13252)  BSMI (EMC: CNS 13438, Safety: CNS 14336-1)  *K10 (Metal Housing)</p>
Operating Temperature	<p>Starting Temperature: 0°C ~ 50°C (32°F ~122°F)  Working Temperature: -10°C ~ 50°C (14°F ~122°F)</p>
Humidity	90% RH (non-condensing)

### System Requirements

Operating System	<p>Microsoft Windows 10/8/7  Mac 10.12 (Chrome only)</p>
Web Browser	<p>Chrome 58.0 or above  Internet Explorer 11</p>
Other Players	VLC: 1.1.11 or above

### Included Accessories

Packing Contents	Quick installation guide, alignment sticker, screw pack, mounting bracket
------------------	---

### DORI (EN 62676-4 Standard)

Detection (25PPM/ 8PPF)	30.3 m (99.4 ft)
Observation (63PPM/ 19PPF)	12.0 m (39.4 ft)
Recognition (125PPM/ 38PPF)	6.1 m (20.0 ft)
Identification (250PPM/ 76PPF)	3.0 m (9.8 ft)