



## LED-1906HDMT

Full HD resolution, LED-backlit, mid-size LCD monitor housed in a durable metal case with a front control membrane. Built for active use in public spaces, this monitor is versatile and effective for any commercial video application.

### Benefits

- Displays Full HD (1920 x 1080) signals (1080i/p) with no downscaling
- 3D + 3D image processing with digital noise reduction
- Built-in ATSC / Clear QAM Tuner
- Durable Metal Housing
- Built-in speakers
- 75mm VESA pattern for mounting
- IR remote control
- Includes Hospitality Features: Maximum volume, Key Lock, Scan Lock, and Auto Reset which maintains Startup Channel, Power On Volume, and Power On Source

### Accessories

- DS-1906M: Desk stand for LED-1906HDMT
- WM-32: Wall mount bracket (fixed/tilting)
- WM-302: Wall mount with swing arm & 4-way adjustable
- WMC-2346: Ceiling mount bracket for 1.5" NPT pipe

### Related Products

- LED-1906HDMTL: Flush mount version
- LED-1906HDMTR: Rack mount version

| Specifications              |  |
|-----------------------------|--|
| Mount                       | VESA 75 x 75mm   |
| Screen Panel                | 18.5" TFT Active Matrix  |
| HD Compatible               | Yes  |
| Anti Glare Coating          | Yes  |
| Case                        | Durable Metal  |
| IR Remote Control           | Yes  |
| Native Aspect Ratio         | 16:9   |
| Visible Screen Size (WH)    | 16.1" x 9.1" / 409.8 x 230.4mm                                 |
| Resolution                  | 1920(H) x 1080(V)  |
| Brightness Rating           | 250 cd/m <sup>2</sup> (Nit)                                    |
| Contrast Ratio              | 1200:1   |
| Back Light                  | LED (30K)  |
| Dot Pitch                   | 0.30(H) x 0.30(V)mm  |
| Color Depth                 | 16.7M  |
| Number of Pixels            | 1,049,088  |
| Response Time               | 5ms (Rising/Falling)   |
| Audio Power / Speakers      | 8 Ohm, 2 Speakers x 2 Watts                                    |
| Viewing Angle (L/R/T/B)     | 89/89/89/89 degrees  |
| Digital Signal Processing   | 3D comb filter image processing and 3D digital noise reduction |
| Dimensions                  | 17.51" x 11.89" x 1.4" / 445 x 302 x 36mm                      |
| Operating Temp              | 6 ~ 104°F / -14 ~ 40°C   |
| Power Requirements          | 100 ~ 240 VAC; 50/60Hz   |
| Power Consumption           | <25 Watts; <= 0.5 Watts (Stand-by)                             |
| TV (ATSC/QAM Digital Tuner) | x1 F (Coax) Input  |
| HDMI                        | x2 Inputs  |
| VGA (RGB)                   | x1 15-pin mini D-sub Input                                     |
| Composite                   | x1 RCA Input   |
| USB                         | x1 Input for firmware updates only                             |
| Audio                       | x1 RCA L/R Input; x1 3.5mm earphone Output                     |
| Weight                      | Net: 8.8 lbs / 4 kg; Gross: 11 lbs / 5 kg                      |

Specifications subject to change.