THE CODALE CONIC CANOPY

Data Sheet



The Codale Conic is a steel freestanding canopy which is covered with a waterproof tensile fabric roof. (Please note: the image shows a double Codale Conic.)

0800 389 9072
www.ablecanopies.co.uk
sales@ablecanopies.co.uk

Dimensions:

Length:	3m - unlimited (up to 10m for a single canopy)
Width/Projection:	3m - unlimited (up to 10m for a single canopy)
Height:	4.1m to 4.7m
Spacing Between Posts:	Up to 10 metres depending on size

Features:

Wall Mounted or Freestanding:	Freestanding
Suitable for:	Education | Hospitality | Leisure | Retail | Commercial | Healthcare
Guarantee:	10 years for the frame and 5 years for the fabric
Life Expectancy:	15 years
Maintenance:	Requires only periodic cleaning
Installation Type:	Permanent
Retractable/Collapsible:	No
Method of Fixing:	Posts are installed into the ground with steel base plates into pad stones, the size of which depends on the size of the structure

Frame Specifications:

Construction Material:	Frame: From up to 80mm x 150mm steel box sections Posts: From up to 80mm x 150mm steel box sections
Guttering:	Integrated into the canopy posts
Frame Finish:	Powder coated and galvanised or galvanised only
Colour Options:	Supplied in any of the standard RAL colours shown overleaf Other RAL colours are available however, they may incur additional costs
Fixings:	Steel fixings

Roof Specifications:

Roof Frame:	Steel roof bars
Roof Covering:	Polyester 1100 dtex waterproof tensile fabric with a weight of 650 g/sqm
UV Protection:	Up to 100% protection from harmful UVa and UVb rays
Light Transmission:	The amount of light transmittance depends on the colour chosen
Strength:	The tensile fabric has a strength of 250/230 da N/5 cm
Colour Options:	Available in a range of colours as shown overleaf
Temperature Resistance:	-30°c to +70°c

International Standards:

Fire Ratings:	Fabric: Fire retardant to British standards BS7157, BS7837 and European M2 classification
Strength Tests:	Fabric tensile strength: 250/230 daN/5cm Fabric tear strength: 30/30 daN
CE Marked	Yes to UKCA BS EN1090-1:2009+A1:2011

Colour Options:

	Standard Colours	Non Standard Colours (Additional costs may apply)
Framework	Our standard RAL colours are:	N/A
Tensile Roof Covering		N/A

Weather Protection:


UV

Available Upgrades:

Post Pads	✓
Signage	×
Polycarbonate Side & Front Fills	×
Tensile Fabric Side Panels	✓
Rainbow Package	✓
Roller Shutters	✓
Coloured Polycarbonate	×
Heaters and Lighting	✓

Technical Files Available:

PDF CAD File	✓
DXF CAD File	✓
IGES CAD File	✓
STL CAD File	✓
BIM File	✓
NBS Spec	✓



0800 389 9072

www.ablecanopies.co.uk

sales@ablecanopies.co.uk

9-11 Faraday Close, Gorse Lane Industrial Estate, Clacton on Sea, Essex CO15 4TR