THE ULLSWATER APEX CANOPY

Data Sheet

The Ullswater Apex is a strong freestanding canopy that can be used as a free standing canopy, entrance canopy or external covered walkway.

Dimensions:

Length: Unlimited

Width: Up to 6 metres

Height: 2.8m at apex (as standard)

Spacing Between Posts: Up to 6 metres



www.ablecanopies.co.uk sales@ablecanopies.co.uk

Features:

Wall Mounted or Freestanding: Freestanding

Suitable for: Education | Hospitality | Leisure | Retail | Commercial | Healthcare

Guarantee: N/A

Life Expectancy: Up to 25 Years

Maintenance: Requires only periodic cleaning

Installation Type: Permanent

Retractable/Collapsible: No

Method of Fixing: Posts are installed into the ground with 300mm x 300mm x 10mm steel base plates into

600mm x 600mm x 600mm pad stones into the ground - the size of the pad stones can vary

depending on site specifics

Frame Specifications:

Construction Material: 120m x 60mm x 3.6mmsteel box section

Guttering: Deep flow guttering with uPVC downpipes fitted as standard

Frame Finish: Powder coated

Also available galvanised at an additional cost

Colour Options: Supplied in any standard RAL colour

Other RAL colours are available however, they may incur additional costs $% \left(1\right) =\left(1\right) \left(1\right) \left$

Fixings: 316 marine grade stainless steel fixings

Roof Specifications:

Roof Frame: Fully aluminium roof frame including aluminium roof bars

Roof Covering: 35mm structured polycarbonate panels

UV Protection: Over 98% | This also means the roof panels will not turn yellow over time due to UV degradation

Light Transmission: The polycarbonate offers 63% for clear panels and 31% for opal panels

Strength: Vandal and shatter resistant | 200 times stronger than glass

Colour Options: Available in clear and opal

Temperature Resistance: From -20°c to +100°c

International Standards:

Fire Ratings: Roof panels: European standard BS476 Part 7 class 1fire and EN 13501 B-S1, D0.

CE Marked Yes to UKCA BS EN1090-1:2009+A1:2011

Colour Options: Standard Colours Non Standard Colours (Additional costs may apply) Steel Framework Our standard RAL colours are: Any RAL colour 9910 3000 1023 6018 6005 9005 7016 7012 7001 5015 5005 **Aluminium Roof** Any RAL colour Bars 9910 Polycarbonate N/A **Roof Covering** Clear Opal 9910

Weather Protection:










Available Upgrades:	
Post Pads	✓
Signage	\checkmark
Polycarbonate Side & Front Fills	✓
Tensile Fabric Side Panels	×
Rainbow Package	\checkmark
Roller Shutters	\checkmark
Coloured Polycarbonate	×
Guttering and uPVC downpipes	N/A supplied as standard
Gable Ends	✓

Technical Files Available:	
PDF CAD File	✓
DXF CAD File	✓
IGES CAD File	✓
STL CAD File	✓
BIM File	✓
NBS Spec	✓
STL CAD File BIM File	✓ ✓ ✓





















0800 389 9072

www.ablecanopies.co.uk sales@ablecanopies.co.uk