THE WHITESIDE CANOPY

Data Sheet

The Whiteside is a cost effective structure which has an unlimited length, enabling it to provide extensive cover from the weather. It is perfect for use as a freestanding canopy or entrance canopy within a wide range of setting including schools, colleges, hospitals, care homes and industrial areas.

Dimensions:

Length: Unlimited

Width: Up to 4 metres

Height: To your specification

Spacing Between Posts: Up to 4 metres



www.ablecanopies.co.uk sales@ablecanopies.co.uk

Features:

Wall Mounted or Freestanding: Available as wall mounted or freestanding

Suitable for: Education | Hospitality | Leisure | Retail | Commercial | Healthcare

Guarantee: N/A

Life Expectancy: Up to 25 Years

Maintenance: Requires only periodic cleaning

Installation Type: Permanent

Retractable/Collapsible: No

Method of Fixing: Posts are installed into the ground with 250mm x 2500mm x 8mm steel base plates into

300mm x 300mm x 600mm pad stones

Frame Specifications:

Construction Material: 90mm x 4mm steel hollow tube section

Guttering: None as standard - available at an additional cost

Frame Finish: Powder coated

Also available galvanised at an additional cost

Colour Options: Supplied in any standard RAL colour

Other RAL colours are available however, they may incur additional costs

Fixings: 316 marine grade stainless steel fixings

Roof Specifications:

Roof Frame: Steel roof frame with steel roof bars and aluminium rafter bars

Roof Covering: Choice of 5mm solid or 16mm structured polycarbonate panels

UV Protection: Over 98% | This also means the roof panels will not turn yellow over time due to UV degradation

Light Transmission: The 16mm polycarbonate offers 73% for clear panels and 35% for opal panels

The 5mm polycarbonate offers 92% for clear panels and 47% for opal panels

Strength: Vandal and shatter resistant | 200 times stronger than glass

Colour Options: Available in clear and opal

Temperature Resistance: From -20°c to +100°c

International Standards:

Fire Ratings: Roof panels: European standard BS476 Part 7 class 1fire and EN 13501 B-S1, D0.

CE Marked Yes to UKCA BS EN1090-1:2009+A1:2011

Colour Options: Standard Colours Non Standard Colours (Additional costs may apply) Steel Framework Our standard RAL colours are: Any RAL colour 9910 3000 1023 6018 6005 9005 7016 7012 7001 5015 5005 **Aluminium Roof** Any RAL colour **Rafter Bars** 9910 **Polycarbonate** N/A **Roof Covering** Clear Opal 9910


Weather Protection:



Available Upgrades:	
Post Pads	✓
Signage	✓
Polycarbonate Side & Front Fills	✓
Tensile Fabric Side Panels	×
Rainbow Package	✓
Roller Shutters	×
Coloured Polycarbonate	×
Guttering and uPVC downpipes	✓
Gable Ends	N/A

Technical Files Available:	
PDF CAD File	✓
DXF CAD File	✓
IGES CAD File	✓
STL CAD File	✓
BIM File	✓
NBS Spec	✓





















0800 389 9072

www.ablecanopies.co.uk sales@ablecanopies.co.uk