

IXG-MK

IP Video Guard Station

The IXG-MK is an IP video guard station with a 7" LCD touchscreen for the IXG Series multi-tenant system. A guard unit can have up to 8 IXG-MK stations. The IXG-MK station can place or receive calls from other stations in the system. Once the call is answered, communication can be hands-free (VOX) or full duplex (handset).

Touching the key button will unlock a door or entrance station during communication. The IXG-MK can have up to 9,999 units in its address book and it will maintain a history of calls that it has received. A microSD™ card can be added to record calls that are placed to the IXG-MK IP video guard station.



- 7" TFT color LCD touchscreen
- Color video camera with privacy shutter
- 9,999 unit address book
- View ONVIF® Profile S cameras
- Multi-angled desk stand included (30°, 45°, 60°)
- Slot for microSD™ card (not provided by Aiphone)
- PoE (802.3af)
- 2 contact outputs, 4 trigger inputs
- 8Ω 0.5W speaker output
- 600Ω audio input

Power Source	PoE (802.3af)
Network Interface	10 BASE-T/100 BASE-TX Ethernet (RJ-45)
Protocols	IPv4, IPv6, TCP, UDP, SIP
Bandwidth Usage	Audio (G.722): 64Kbps x 2 for communication, 64Kbps for monitoring Video (H.264): 32Kbps–2,048Kbps
Video Stream	ONVIF® Profile S
Communication	Hands-free (full-duplex), push-to-talk (simplex), or handset (full-duplex)
Video Display	7" LCD touchscreen
Door Release	N/O dry contact, 24V AC/DC, 1A
Mounting	Wall or desk mount (stand included)
Wire Type	Cat-5e or Cat-6
Distance	Master Station to Network Node: 330'
Dimensions	8-1/16" H x 11" W x 2-3/16" D