

ADC-SG130

SPECIFICATIONS

ETHERNET CONNECTION

10 / 100 Mbps (FAST) WAN connection

WI-FI CONNECTION

802.11 b/g/n, 2.4 GHz

DIMENSIONS

3.5 X 3.1 X 1.2" (11.6 x 8.0 x 3.1cm)

LED INDICATORS

4

BUTTONS

Function, WPS, Reset

OPERATING TEMPERATURE

32 - 104°F (0°C - 40°C)

OPERATING HUMIDITY

0 - 80% (non-condensing) RH

REQUIREMENTS

POWER

12 VDC Power Adapter

NETWORK

Broadband Internet connection with router



Smart Gateway

With a reliable wireless connection and excellent range, the ADC-SG130 makes it easy to install any Alarm.com Wi-Fi camera. The ADC-SG130 features WPS, eliminating the need to update cameras with complicated router passwords. Simply plug the ADC-SG130 into any wall outlet, connect to the existing router, pair with a Wi-Fi camera, and enjoy instant, secure connectivity.

FEATURES

- Wi-Fi Access Point (2.4 GHz)
- Reliable network for Alarm.com Wi-Fi cameras, ensuring cameras stay connected when the home's network SSID, password, or ISP changes
- Remote management and troubleshooting
- Enhanced customer experience

IN THE BOX

- ADC-SG130 Smart Gateway
- Power adapter
- Ethernet cable
- Quick installation guide

LED GUIDE

		LED STATUS	DESCRIPTION
POWER		On	Device powered on
		Off	Device powered off
		Flashing	Device booting
DATA		On/Flashing	Device transferring/receiving data over Ethernet
		Off	No data is being transferred over Ethernet. Please check the Ethernet connection between the Smart Gateway and the Router
COMMUNICATION		On	Connected to Internet
		Off	No local or Internet connection
		Flashing (slowly)	Local connection, no Internet
		Flashing (5 quick blinks)	Communication test initiated
WI-FI		On	Active
		Off	Inactive
		Flashing	WPS mode
ADDITIONAL STATES		All LEDs Flashing (escalating)	Firmware upgrade in progress
		All LEDs Flashing (simultaneously)	Reset in Progress