

4MP Outdoor Floodlight Camera

ADC-V729
DATA SHEET

Key Features

- 4MP Video
- 3000 Lumen Floodlight
- PIR Motion sensor for floodlight activation
- Red/blue warning light
- Onboard Recording with Smart View
- Video Analytics with People, Animal, and Vehicle Detection
- Perimeter Guard™ and Manually Triggered Warning Sounds+Lights for proactive deterrence

Requirements

Power:
DC 24V DC PSU



Overview

The ADC-V729, a 4 MP outdoor Wi-Fi floodlight camera with Two-Way Audio, provides the next level of awareness and security. Deter intruders with powerful strobing floodlights, flashing red/blue warning lights, and a powerful speaker. Customize the lights to your needs with multiple options such as Person/Vehicle/Animal detection triggers or motion triggers and choosing between full floodlight or strobing effects. With high quality 4MP video you will never miss a detail day or night. Plus, Onboard Recording with Smart View provides 24/7 coverage with locally recorded encrypted video.

Specifications

Image sensor: 4MP 1/2.7" format

Recording Compression: H.264

Live resolution options:
Up to 2688 x 1520

Recording resolution options:
Up to 2688 x 1520

Horizontal Field of View: 117

Vertical Field of View: 62

Diagonal Field of View: 141

Wi-Fi: Dual band 802.11 b/g/n/ac 2 x 2

Ingress Protection: IP 66

Low Light Sensitivity: 0.5 lux

IR Range: 15 meter

Lights: 4000K, 3000 Lumens Floodlights

Image adjustments:
Flip, brightness, contrast, saturation, sharpness, exposure

Operating Temperature: -20C - 50C

Operating Humidity: 20% - 100%

Dimensions (L x W x H):
305 x 235 x 198 mm



4MP Outdoor Floodlight Camera

ADC-V729AC DATA SHEET

Key Features

- 4MP Video
- 3000 Lumen Floodlight
- PIR Motion sensor for floodlight activation
- Red/blue warning light
- AC Hardwired (100-240V)
- Onboard Recording with Smart View
- Video Analytics with People, Animal, and Vehicle Detection
- Perimeter Guard™ and Manually Triggered Warning Sounds+Lights for proactive deterrence

Requirements

Power:
AC 100-240V



Overview

The ADC-V729AC, a 4 MP outdoor Wi-Fi floodlight camera with Two-Way Audio, provides the next level of awareness and security. Deter intruders with powerful strobing floodlights, flashing red/blue warning lights, and a powerful speaker. Customize the lights to your needs with multiple options such as Person/Vehicle/Animal detection triggers or motion triggers and choosing between full floodlight or strobing effects. With high quality 4MP video you will never miss a detail day or night. Plus, Onboard Recording with Smart View provides 24/7 coverage with locally recorded encrypted video.

Specifications

Image sensor: 4MP 1/2.7" format

Recording Compression: H.264

Live resolution options:
Up to 2688 x 1520

Recording resolution options:
Up to 2688 x 1520

Horizontal Field of View: 117

Vertical Field of View: 62

Diagonal Field of View: 141

Wi-Fi: Dual band 802.11 b/g/n/ac 2 x 2

Ingress Protection: IP 66

Low Light Sensitivity: 0.5 lux

IR Range: 15 meter

Lights: 4000K, 3000 Lumens Floodlights

Image adjustments:
Flip, brightness, contrast, saturation, sharpness, exposure

Operating Temperature: -20C - 50C

Operating Humidity: 20% - 100%

Dimensions (L x W x H):
305 x 235 x 198 mm

4MP Outdoor Floodlight Camera

ADC-V729P DATA SHEET

Key Features

- 4MP Video
- 3000 Lumen Floodlight
- PIR Motion sensor for floodlight activation
- Red/blue warning light
- PoE++ powered
- Onboard Recording with Smart View
- Video Analytics with People, Animal, and Vehicle Detection
- Perimeter Guard™ and Manually Triggered Warning Sounds+Lights for proactive deterrence

Requirements

Power:
DC 24V DC PSU or PoE ++ (802.3bt)

Ethernet Connection:
10/100Mbps RJ-45



Overview

The ADC-V729P, a 4 MP outdoor Wi-Fi floodlight camera with Two-Way Audio, provides the next level of awareness and security. Deter intruders with powerful strobing floodlights, flashing red/blue warning lights, and a powerful speaker. Customize the lights to your needs with multiple options such as Person/Vehicle/Animal detection triggers or motion triggers and choosing between full floodlight or strobing effects. With high quality 4MP video you will never miss a detail day or night. Plus, Onboard Recording with Smart View provides 24/7 coverage with locally recorded encrypted video.

Specifications

Image sensor: 4MP 1/2.7" format

Recording Compression: H.264

Live resolution options:
Up to 2688 x 1520

Recording resolution options:
Up to 2688 x 1520

Horizontal Field of View: 117

Vertical Field of View: 62

Diagonal Field of View: 141

Wi-Fi: Dual band 802.11 b/g/n/ac 2 x 2

Ingress Protection: IP 66

Low Light Sensitivity: 0.5 lux

IR Range: 15 meter

Lights: 4000K, 3000 Lumens Floodlights

Image adjustments:
Flip, brightness, contrast, saturation, sharpness, exposure

Operating Temperature: -20C - 50C

Operating Humidity: 20% - 100%

Dimensions (L x W x H):
305 x 235 x 198 mm