



Pro Series Commercial Camera Mounting Plates Data Sheet

ADC-VACC-MNT110 & ADC-VACC-MNT130
www.alarm.com

© 2021 Alarm.com. All rights reserved. 210507

Specifications

ADC-VACC-MNT110

Camera compatibility: VC827P, VC728PF, V724

Mounting base compatibility:

Conduit Box: CB110
Angled Base: AB110
Ceiling Mount: PC110 + CPM
Wall Mount: PC110 + WMS OR WM110
Corner Mount: PC110 + WMS + CM
Pole Mount: PC110 + WMS + PM

Dimensions (D x H): 4.4 x 0.4" (11.1 x 1.0 cm)

Weight: 3.3 oz (94 g)

ADC-VACC-MNT130

Camera compatibility: VC847PF, VC838PF

Mounting base compatibility:

Conduit Box: CB130T, CBM
Angled Base: ABM
Wall Mount: PC130T + WML
Corner Mount: PC130T + WML + CM
Pole Mount: PC130T + WML + PM

Dimensions (D x H): 5.0 x 0.5" (12.8 x 1.2 cm);
Flange diameter of 5.4" (13.8 cm)

Weight: 5.2 oz (147 g)

ADC-VACC-MNT110



ADC-VACC-MNT130



Overview

The ADC-VACC-MNT110 and ADC-VACC-MNT130 camera mounting plates enable easy mounting of Alarm.com Pro Series cameras to third-party camera mounting bases. This is especially useful in takeovers where these mounting bases are already installed, saving time and money during installation.

These camera mounting plates are optional and are not required when mounting a Pro Series camera directly to a wall or ceiling.

Included Accessories

- ADC-VACC-MNT110 Mounting Plate
 - M3x10 truss head screws (x3) for mounting adapter to CB110
 - M4x10 pan head screws (x3) for mounting adapter to AB110, PC110
 - M5x10 pan head screws (x3) for attaching VC728PF, V724
 - M4x16 cheese head screws (x3) for attaching VC827P
 - ST4.8 self-tapping screws and anchors (x3) for attaching to wall/ceiling
 - Cable plug for weather proofing
- ADC-VACC-MNT130 Mounting Plate
 - M4x10 pan head screws (x3) for mounting adapter to CB130T, CBM, ABM
 - M5x10 pan head screws (x3) for attaching VC838PF
 - M4x22 cheese head screws (x3) for attaching VC847PF
 - ST4.8 self-tapping screws and anchors (x3) for attaching to wall/ceiling
 - Cable plug for weather proofing

Features

- Adapts Alarm.com cameras to third-party mounting bases
- Compatible with a variety of third-party bases
- Minimize installation costs and time