

ADC-W110

SPECIFICATIONS

WI-FI SECURITY

WEP, WPA, WPA2 Wi-Fi

ETHERNET INTERFACE

10 / 100 Mbps RJ-45 IEEE 802.3 af PoE

WIRELESS

IEEE 802.11 b / g / n 2.4 GHz

DIMENSIONS (W x L x H)

2.4 x 2.2 x 3.6"

OPERATING TEMPERATURE

32°F - 113°F (0°C - 45°C)

OPERATING HUMIDITY

< 90%

OPERATING VOLTAGE

Min: 100 V, Max: 120 V

REQUIREMENTS

POWER

Standard electrical outlet

NETWORK

Broadband Internet connection with router

SETUP

Access Point (AP) mode or
Wi-Fi Protected Setup (WPS) mode



PoE to Wi-Fi Bridge

The ADC-W110 makes it easy to install any Alarm.com Power over Ethernet (PoE) camera, eliminating the need to run cable wiring throughout a home or business. Simply plug the device into a wall outlet to provide a PoE camera with both electrical power and secure, reliable Wi-Fi connectivity. The ADC-W110 integrates with Alarm.com, providing easy post-installation troubleshooting and enhanced security.

FEATURES

- Simple plug-in installation
- Secure, reliable Wi-Fi connectivity
- Eliminate the need for wires

LED GUIDE

		LED STATUS	DESCRIPTION
POWER		Solid Green	Powered on
		Off	Powered down
STATUS		Solid White	Successfully connected to the wireless network
		Solid Green	
		Solid White	Local network connection only, connecting to Internet
		Blinking Green	
WPS MODE		Off	WPS mode
		Blinking Green	
AP MODE		Blinking White	AP mode
		Off	
ERROR		Blinking Red	No network found
		Off	
FACTORY RESET		Blinking Red	Restore factory-default settings
		Blinking Red	