

Rechargeable Batteries

Sealed lead acid (SLA)

Altronix rechargeable batteries supply 12VDC for security, access, surveillance and fire applications.



Key Features

- For general purpose, up to 5 years in standby service or more than 260 cycles at 100% discharge
- Sealed non-spillable lead acid batteries
- Highly efficient, leak proof and maintenance free

Rechargeable Batteries Reference Chart

Altronix Model Number	Output Voltage	A/Hr	Dimensions				Weight	
			Length	Width	Height	Overall Height	Product	Shipping
BT124	12VDC	4	3.54" (90mm)	2.75" (70mm)	3.93" (100mm)	4.13" (105mm)	2.3 lb. (1.04 kg)	2.8 lb. (1.27 kg)
BT126		7	5.94" (151mm)	2.55" (65mm)	3.70" (94mm)	3.93" (100mm)	4.15 lb. (1.88 kg)	4.65 lb. (2.11 kg)
BT1212		12	5.94" (151mm)	3.85" (98mm)	3.74" (95mm)	3.97" (101mm)	8.3 lb. (3.76 kg)	8.8 lb. (4.0 kg)
BT1240		40	7.71" (196mm)	6.49" (165mm)	6.88" (175mm)	6.88" (175mm)	26.4 lb. (12 kg)	27.2 lb. (12.34 kg)