



1802 SERIES

TELEPHONE ENTRY SYSTEM



User-friendly Integrated Design Features

- Visitors use the phone system to communicate with a resident who can grant or deny access via their own touch-tone telephone
- Slim design for applications with limited space. Surface or flush mount styles available
- Hands free full duplex voice communication
- 1802, 1802-AP (Access Plus), 1802-EPD (Electronic Programmable Directory) provides service for up to 600 residents, 27 residents, and 100 residents respectively
- 2 year limited factory warranty

1802-EPD

RESIDENTIAL • MULTI-HOME • SMALL APARTMENT



Modular Design
makes installation and service easy



Mounting Kiosk
available for flush mount models



Flush or Surface
mount available for 1802 & 1802-EPD,
surface mount only for 1802-AP




1802-AP PC Programmable
free software download from
doorking.com/software


ACCESS CONTROL SOLUTIONS



1802 SERIES TELEPHONE ENTRY SYSTEM




1802 EPD




1802/1802 AP

Surface
Mount



1802 EPD



1802

Flush
Mount

MODEL	1802	1802-EPD	1802-AP ⁷
MAX PHONE NUMBERS	600	100	27
DIRECTORY NAMES ⁶	N/A	100	N/A
ENTRY CODES ¹	1000	100	0
DEVICE CODES ²	0	0	100
RELAYS	2	2	2
AUXILIARY INPUTS ³	1	1	2
EXPANSION ⁴	No	No	6 Max
PC PROGRAMMABLE ⁵	No	No	Yes
TEMPORARY CODES	5	5	10
HOLIDAY SCHEDULE	No	No	Yes

- Entry codes are four (4) digits only and are not the same as device codes. Entry codes grant access when entered on the entry system keypad (or secondary keypad) only.
- Device codes refer to any five (5) digit RS-485 device used to access an entry point, such as cards, transmitters or PINs (Personal Identification Number). Five (5) digit device codes can also be used on the system keypad.
- 1802 and 1802EPD, auxiliary input allows a switch closure to activate relay 2, or can be set to auto-dial a preprogrammed telephone number. 1802 AP uses a standard RS-485 data input.
- Six (6) additional entry points can be controlled via RS-485 card readers, AVID tag readers, RF receivers or digital keypads.
- AP Programming software available for free download at doorking.com/software
- Single line 16 character 5/16 LCD display.
- Access Plus model does not have any programming display or electronic directory.

TECHNICAL FEATURES

MECHANICAL

- Stainless steel faceplate
- Galvanized steel sub-plate
- Metal keypad
- Offset speaker holes for protection
- Hands free voice operation (Optional handset available on surface mount only)
- Built-in postal lock provision

ELECTRICAL

- 16 VAC (power transformer included)
- Full Duplex voice communication
- Two relays allow for control of both a vehicular gate and a pedestrian gate

1802

- Stores up to 600 phone numbers
- Special input can be programmed for relay activation or dial-out function
- Time zone restrictions on selected entry codes
- LCD display for programming assistance and shows 'open' when access is granted
- Four-digit entry codes = 1000

1802-EPD

- Single-line 16 character LCD directory
- Stores up to 100 phone numbers
- Lighted keypad and A-Z-CALL buttons
- Four-digit entry codes = 100

1802-AP

- Up to 27 phone numbers (23 with intercom)
- 100 device codes (card, keypad, transmitter)
- 20 digit dialing capability
- 500 event history buffer
- 10 temporary access codes
- Add 6 additional entry points (RS485) using card, keypad, or proxy RF devices
- Relay board available which allows use of existing 26-bit wiegand devices
- Holiday schedule
- Four (4) hold open time zones
- Schedule un-lock / lock times
- Email notifications

1802 AND 1802-EPD

- Programmable directory codes (1 to 4 digits)
- 16 digit dialing capability
- DTMF tone output allows for use with PBX and auto-attendant type phone systems
- Five-digit entry codes = 6
- Built-in clock / calendar
- Time clock has its own backup power source
- Hold open time zones (4)
- Entry code time zones
- Flash entry codes

MISCELLANEOUS

- Environmental: 10°F to 145°F (-12°C to 62°C)
- ADA Compliant handset kit (P/N 1807-012) available on surface mount only
- Camera Ready: Optional Color CCTV camera*
*may require additional CCTV equipment
- Shipping weight approximately 15-20 Lbs (6.8-9 kg)



1802/1802 EDP



1802 AP

DoorKing®, Inc.

Access Control Solutions since 1948

120 S. Glasgow Avenue,
Inglewood, California 90301 U.S.A.
Tel: 310-645-0023 FAX: 310-641-1586
www.doorking.com

© 2021 All Rights Reserved. Product specifications may change without notice. Rev. 3/21

MEMBER:



FCC (US) DUF6VT-12874-OT-T
DOC (CAN) 1736 4507 A

DISTRIBUTED BY: