

SINGLE ZONE ANNUNCIATORS MODEL SZA310 and SZA320



FEATURES:

- Monitor Single EOL Resistor Supervised Closed or Open Circuit
- Simple Visual Display with Audible
 - Push Button or Key-Switch Arm/Disarm/Reset
- Two SPDT, 2 Amp, Relays, one with Timer
- Recessed or Surface Mount

SPECIFICATIONS

MOUNTING	Recessed and Surface Mount
SIZE	4 1/2" X 4 1/2" X 2 1/2"
COLOR	Brushed Stainless Steel Faceplate Optional White Plastic Back Box
POWER	12 - 24 VAC or VDC
INPUTS	Closed or Open Circuit EOL (End of Line) Resistor Loop, 1 K Ohm Secure
OUTPUTS	Green LED = Secure Yellow LED = Disarmed Red LED = Alarm Audible - Low Level Piezo when Alarm 24VDC, 2 Amp, SPDT Relay
OTHER	Call to request other options and features



Call Flair for Magnetic Contacts, Water Sensors, Vibration Sensors, Pull-Apart Switches and other sensors for the SZA300

OPERATION: Flair Single Zone Annunciators are attractive, low cost alarms that can be used in a wide range of applications such as door / window alarms, pool alarms, emergency exits, HVAC equipment protection, leak detection and any other situation where a sensor needs to be monitored and a bypass capability is desired. Green, Yellow, Red LEDs and built in sounder identify with a glance exactly what is happening with the security system. Two SPDT relays can be connected to sirens, cameras, shut off valves or other devices.