



Better sound quality.
Better features.
Better price.

JA **AUDIO**™

Speakers to Fit Every Need and Every Lifestyle.

I30C




Watts/RMS: 30
Mounting: Cam-Lock
Grille: White Metal
Frequency: 48 Hz - 20 kHz
Overall Dimensions: 9 1/2" DIA x 3" DPT
Install Dimensions: 7 1/2" DIA
Tweeter Type and Size: Mylar 1/2"
Magnet Weight: 10 oz
Cone Type and Size: 6 1/2" Coated Paper
Db Sensitivity: 88 db
Impedance: 8 Ω nominal
Speaker Bracket: SPKBKT-6C
Warranty: Intrasonic 10 Year

I100C



Watts/RMS: 100
Mounting: Cam-Lock
Grille: White Metal
Frequency: 36 Hz - 22 kHz
Overall Dimensions: 10 3/4" DIA x 3 1/2" DPT
Install Dimensions: 9 1/4" DIA
Tweeter Type and Size: 360° Directional Laminated Alum PP1
Magnet Weight: 13.3 oz
Cone Type and Size: 8" Laminated PP
Db Sensitivity: 89 db
Impedance: 8 Ω nominal
Bass and Treble: 3 Position Adjustable
Speaker Bracket: SPKBKT-8C
Warranty: Intrasonic 10 Year

EX-206C




Power Handling: 5-100
Mounting: Cam-Lock
Grille: White Aluminum
Frequency: 55 Hz - 22,000 Hz
Dimensions: 9 1/8" DIA x 5 1/4" DPT
Install Dimensions: 8 3/8" DIA
Cone Type and Size: 6.5" Yellow Fiberglass Cone with a Rubber Surround
Crossover: Hi-End 18 dB, Adjustable for Tweeter Level $\pm$ 3 dB
Angel Degree: 20
Tweeter: 1" Titanium Dome Swivel
Efficiency: 89 db
Impedance: 8 Ω nominal, 6 Ω minimum
Speaker Bracket: SPKBKT-6C
Warranty: Intrasonic 10 Year

JA-C8AII



Power Handling: 10-150
Mounting: Cam-Lock
Grille: White Aluminum
Frequency: 42 Hz - 22,000 Hz
Overall Dimensions: 11" DIA x 3 1/2" DPT
Install Dimensions: 9 1/2" DIA
Cone Type and Size: 8" Aluminum Cone with a Rubber Surround
Crossover: 18 dB High - Low pass
Adjustable Crossover: Tweeter 0/-3 dB
Tweeter: 1" Aluminum Dome Swivel with Ferrofluid Cooled Voice Coil
Efficiency: 91 db
Impedance: 8 Ω nominal, 6 Ω minimum
Speaker Bracket: SPKBKT-8C
Warranty: Intrasonic 10 Year

EX-C80II



Power Handling: 45-150
Mounting: Cam-Lock
Grille: White Aluminum
Frequency: 40 Hz - 20 kHz $\pm$ 3 dB
Overall Dimensions: 10 3/4" DIA x 5 1/4" DPT
Install Dimensions: 9 1/2" DIA
Cone Type and Size: 8" Yellow Fiberglass Cone with Rubber Surround
Crossover: Hi-End 12 dB, Adjustable for Tweeter & Woofer
Tweeter: 1" Titanium Dome Swivel
Tweeter with Ferrofluid Cooled Voice Coil
Db Sensitivity: 88 db
Impedance: 8 Ω nominal, 6 Ω minimum
Speaker Bracket: SPKBKT-8C
Warranty: Intrasonic 10 Year

I100W



Power Handling: 100
Mounting: Cam-Lock
Grille: White Metal
Frequency: 36 Hz - 22 kHz
Dimensions: 10" W x 14 1/4" H x 3 1/2" DPT
Install Dimensions: 8 7/8" W x 12 7/8" H
Tweeter Type and Size: 360° directional Laminated Alum PP1
Magnet Weight: 13.3 oz
Cone Type and Size: 8" Laminated PP
Db Sensitivity: 89 db
Impedance: 8 Ω nominal
Bass and Treble: 3 Position Adjustable
Speaker Bracket: SPKBKT-8IW
Warranty: Intrasonic 10 Year

JA-SS7



Power Handling: 80 (120 Watts Max)
Frequency: 55 Hz - 600 Hz
Overall Dimensions: 9 7/8" W x 13" H x 14" DPT
Cone Type and Size: 6" x 9" Long-Throw Woofer to Reproduce Low Frequency's
Bass Booster: 20 Hz + 5 dB
Frequency: 18 dB High - Low Pass Auto power input
Signal Level: 5 mv
Impedance: 8 Ω nominal
Warranty: Intrasonic 2 Year

JA-T5



Power Handling: 20-120
Mounting: Bracket
Frequency: 50 Hz - 22,000 Hz
Color: White
Dimensions: 7 1/8" W x 9 1/8" H x 6 9/17" DPT
Cone Type and Size: 5 1/4" Polypropylene with a Rubber Surround
Tweeter: 5/8" liquid-cooled polycarbonate
Sensitivity: 89 dB 1W/1M
Impedance: 8 Ω minimum
Warranty: Intrasonic 2 Year

JA-B3II



Power Handling: 100 (35 Watts Continuous)
Mounting: Adjustable Swivel Bracket Included
Frequency: 250 Hz - 18 kHz
Color: White or Black
Dimensions: 3 1/4" W x 7" H x 4 3/4" DPT
Sensitivity: 91 dB/Wm
Impedance: 6 Ω minimum
Warranty: Intrasonic 10 Year

JA-BT-VC



Stereo Wireless Volume Control
30 Watts
Bluetooth: 3.0+EDR stereo module High efficiency 30Wx2 class D amplifier
Frequency range: 20-20k Hz
Stereo inputs: 3.5mm
Bluetooth® Technology
Approx. 30' Distance

B3-HTPACK



5.1 Mini-Cube Surround Sound
Includes:
 (5) Each JA-B3 Mini Cubes
 (1) JA-SS10 Subwoofer
 (1) I51W Home Theater Wall Plate
Colors: White or Black Mini-Cubes

JA-VNB-75



Power Handling: 75 RMS/150 Max
Attenuation: 34-0 dB in 12 position
Frequency: 35 Hz - 20 kHz
Color: White
Overall Dimensions: 14 1/8" x 10 1/8" x 4"
Warranty: Intrasonic 2 Year

EX-R6T

Power Handling: 5-100
Mounting: Cam-Lock
Grille: White Aluminum
Frequency: 52 Hz - 22,000 Hz
Overall Dimensions: 11" DIA x 6" DPT
Install Dimensions: 9 1/4" DIA
Cone Type and Size: Pivoting 6.5" Yellow Fiberglass Cone with a Rubber Surround
Crossover: Hi-End 12 dB, Adjustable for Tweeter & Woofer Level ± 3 dB
Tweeter: Pivoting 1" Titanium Dome Swivel
Efficiency: 88 db
Impedance: 8 Ω nominal, 6 Ω minimum
Speaker Bracket: SPKBKT-8C
Warranty: Intrasonic 10 Year

JA-I8AII

Power Handling: 100
Mounting: Cam-Lock
Grille: White Metal
Frequency: 36 Hz - 22 kHz
Dimensions: 10" W x 14 1/4" H x 3 1/2" DPT
Install Dimensions: 8 7/8" W x 12 7/8" H
Tweeter Type and Size: 360° directional Laminated Alum PP1
Magnet Weight: 13.3 oz
Cone Type and Size: 8" Laminated PP
Db Sensitivity: 89 db
Impedance: 8 Ω nominal
Bass and Treble: 3 Position Adjustable
Speaker Bracket: SPKBKT-8IW
Warranty: Intrasonic 10 Year

JA-I6AII

Power Handling: 10-100
Mounting: Cam-Lock
Grille: White Metal
Frequency: 50 Hz - 22,000 Hz
Dimensions: 8 3/4" W x 12 1/16" H x 3 1/4" DPT
Install Dimensions: 7 1/4" W x 10 1/16" H
Cone Type and Size: 6 1/2" Aluminum Cone with a Rubber Surround
Crossover: 24 dB High - Low pass
Tweeter: 1" Aluminum Dome Swivel With Ferrofluid Cooled Voice
Coil Efficiency: 90 db
Impedance: 8 Ω nominal, 6 Ω minimum
Speaker Bracket: SPKBKT-6IW
Warranty: Intrasonic 10 Year

JA-CC5AII

Power Handling: 10-100
Mounting: Cam-Lock
Grille: White Aluminum
Frequency: 70 Hz - 22,000 Hz
Dimensions: 17 3/4" L x 8 3/4" H x 3" DPT
Install Dimensions: 16 3/8" L x 7 3/8" H
Cone Type and Size: (2) 5 1/4" Aluminum Cone with a Rubber Surround
Crossover: 18 dB High - Low Pass
Adjustable Crossover: Tweeter 0/-3 dB
Tweeter: 3/4" Aluminum Dome
 Tweeter with Ferrofluid Cooled Voice Coil
Efficiency: 89 db
Impedance: 8 Ω nominal
Speaker Bracket: N/A
Warranty: Intrasonic 10 Year

JA-D6AII

Power Handling: 10-100 Watts
Mounting: Cam-Lock
Grille: White Aluminum
Frequency: 55 Hz - 22,000 Hz ± 3 dB
Color: White
Overall Dimensions: 9 1/2" DIA x 3 1/8" DPT
Install Dimensions: 8" DIA
Cone Type and Size: Dual voice coil in-ceiling speaker, 6 1/2" Aluminum Cone with a Rubber Surround
Crossover: 24 dB
Tweeter: (2) 3/4" Aluminum Dome Swivel
 Tweeter with Ferro fluid Cooled Voice Coil
Db Sensitivity: 90 db
Impedance: 8 Ω nominal, 6 Ω minimum
Speaker Bracket: SPKBKT-8C
Warranty: Intrasonic 10 Year

EX-I65II

Power Handling: 5-100 Watts
Mounting: Cam-Lock
Grille: White Aluminum
Frequency: 50 Hz - 22,000 Hz ± 3 dB
Dimensions: 12" W x 8 1/16" H x 3 11/16" DPT
Install Dimensions: 7 1/4" W x 10 3/4" H
Cone Type and Size: 6 1/2" yellow Fiberglass Cone with a Rubber Surround
Crossover: Hi-End 18 dB, Adjustable for Tweeter & Woofer Level $\pm$ dB
Tweeter: 1" Titanium Dome Eyeball
 Swivel Tweeter with Cooled Voice Coil
Efficiency: 90 db
Impedance: 8 Ω nominal, 6 Ω minimum
Speaker Bracket: SPKBKT-6IW
Warranty: Intrasonic 10 Year

JA-PED 4W

**4" 2 Way
 Pendant Speaker
 80 Watts**
Tweeter: 13mm Mylar
Woofer: Polypropylene woofer with rubber surround
Crossover: Hi-6db
Transformer: 100V /8 Ω /20W/10W/5W
Impedence: 8 Ω
Weight: 1.9KG

JA-PED 6B

**6.5" 2 Way
 Pendant Speaker
 100 Watt**
Tweeter: 13mm Mylar
Woofer: Polypropylene woofer with rubber surround
Crossover: Hi-6db
Transformer: 100V /8 Ω /20W/10W/5W
Impedence: 8 Ω
Weight: 2.9KG

JA-70V-C

**8" Dual Cone 70V Ceiling
 Loudspeaker**
 Suitable for any 70V/25V Paging System
 Dual Cone
 70V/ 5W 2.5W 1W 0.5W 0.25W
 25V/ 5W 2.5W 1W 0.5W 0.25W
Resonant Frequency: 110Hz $\pm 15\%$
Dimensions: 12 7/8" x 2 3/4"
Impedance: 8 Ω $\pm 15\%$ @ LOW-Z

JA-VSL-100

Power Handling: 100 RMS/180 Max
Attenuation: 34-0 dB in 12 position
Frequency: 35 Hz - 20 kHz
Color: White
Warranty: Intrasonic 2 Year

JA-RK6-GY

**6.5" Gray Rock Speaker
 100 Watt**
Tweeter: 13mm Mylar
Woofer: 6.5" PP Cone W/Rubber Edge
Crossover: Hi-6db
Impedence: 8 Ω
Weight: 2.8KG

ROCK-RK820

Power Handling: 250
Frequency: 100 Hz - 22 kHz 3 dB
Color: Red
Cone Type and Size: 8" Black Polypropylene Cone
Tweeter: 2" Polypropylene
Impedance: 8 Ω nominal, 6 Ω minimum
Warranty: Intrasonic 2 Year

JA-SS10

Power Handling: 120
(200 Watts Max)

Frequency: 50 Hz - 400 Hz

Dimensions: 14 1/2" W x 15 H x 14 1/2" DPT

Cone Type and Size: 10" Long-Throw
Woofer to Reproduce Low Frequency's

Bass Booster: 20 Hz + 5 dB

Frequency: 50 Hz-400 Hz Auto power input

Signal Level: 5 mv

Impedance: 8 Ω nominal

Warranty: Intrasonic 2 Year



EX-CC6

Power Handling: 35-100

Mounting: Cam-Lock

Grille: White Aluminum

Frequency: 52 Hz - 22,000 Hz

Dimensions: 20 1/4" L x 9" H x 4" DPT

Install Dimensions: 18 3/4" L x 7 3/8" H

Cone Type and Size: (2) 6 1/2" Yellow
Fiberglass Cone with a Rubber Surround

Crossover: Hi-End 12 dB, Adjustable for
Tweeter & Woofer Level ± 3 dB

Tweeter: 1" Titanium Dome Swivel

Efficiency: 88 db

Impedance: 8 Ω nominal, 6 Ω minimum

Speaker Bracket: N/A

Warranty: Intrasonic 10 Year



JA-C6All

Power Handling: 10-100

Mounting: Cam-Lock

Grille: White Aluminum

Frequency: 50 Hz - 22,000 Hz

Overall Dimensions: 9 1/2" DIA x 3 1/8" DPT

Install Dimensions: 8" DIA

Cone Type and Size: 6 1/2" Aluminum
Cone Woofer with a Rubber Surround

Crossover: 18 dB High - Low pass
Adjustable Crossover: Tweeter 0/-3 dB

Tweeter: 3/4" Aluminum Dome with
Ferrofluid Cooled Voice Coil

Efficiency: 89 db

Impedance: 8 Ω nominal

Speaker Bracket: SPKBKT-6C

Warranty: Intrasonic 10 Year



I30W

Power Handling: 30

Mounting: Cam-Lock

Grille: White Metal

Frequency: 48 Hz - 20 kHz

Dimensions: 8 3/4" W x 12" H x 2 1/2" DPT

Install Dimensions: 7 3/8" W x 10 3/4" H

Tweeter Type and Size: Mylar 1/2"

Magnet Weight: 10 oz

Cone Type and Size: 6 1/2" Coated Paper

Db Sensitivity: 88 db

Impedance: 8 Ω nominal

Speaker Bracket: SPKBKT-61W

Warranty: Intrasonic 10 Year



The JA Audio Difference

The sound quality from our products is continually tested against the competition, and we beat them every time. To keep this edge, we observe every stage of production in painstaking detail. From superior materials, design flexibility, reliability and efficiency to quality sound reproduction, we make no compromises. Moreover, we're experts in the delivery of aesthetically pleasing products at a reasonable price. We understand what customers need from a manufacturer like JA Audio, and we make those needs our prime directive.

Don't settle for less, choose JA Audio.

The JA Audio Warranty

JA Audio will repair or replace any defect in material or workmanship which occurs during normal use of every product with new or rebuilt part, free of charge in the USA, ceiling, in-wall speakers and outdoor speakers 10 (ten) years and 2 (two) years for subwoofers from the date of original purchase. This warranty does not cover damages in shipment, failures caused by other products not supplied by JA Audio, or failures due to accident, misuse, or alteration of the equipment. This warranty is extended only to the original purchaser, and a purchase receipt invoice or other proof of original purchase date will be required before warranty repairs are provided.

WS-KIT

**2.4G Wireless
Speaker System**

Includes: Transmitter, Transformer,
Receiver - additional receivers are
available (WS-KIT02)



About Intrasonic Technology

Intrasonic Technology, headquartered in Dallas, TX, manufactures full-featured, easy-to-use music distribution and intercom systems that offer great value for the price. Our diverse line of products includes Music Distribution and Intercom Systems, Video Door Intercom Systems, and a wide variety of ceiling, in-wall, or mini-cube audio speakers, and associated accessories. Product names and model numbers referenced or depicted on this brochure are trademarks or registered trademarks of Intrasonic Technology, Inc.

Learn more today!

Contact your JA Audio
representative shown below,
or for more information, visit
www.intrasonictechnology.com.



An Intrasonic Technology Company