



345S
SECURITY SENSOR

**Security Sensor with On/Off
Switchable Encryption.**

2GIG-FTD100-345

Flood and Temperature Sensor

The 2GIG® Flood and Temperature Sensor provides timely notification before costly water damage. This wireless sensor wherever there is risk of unwanted water pooling.

This versatile device a fully supervised 345 MHz sensor with a unique dual-sensing technology, which employs built-in metal contacts on both its top and bottom to detect leaks without requiring an external probe, making installation exceptionally easy.

The detector supports both encrypted and non-encrypted (default) 345 MHz communications, with an internal switch for mode selection.



**Stock half as many SKUs
on trucks.**

Easily choose encrypted/
non-encrypted operation
with an internal switch.
2GIG 345S sensors work
for any installation.

**Complete 2GIG security
ecosystem.**

345S sensors work with
the all-new GC Touch,
revolutionary 2GIG EDGE,
and earlier security &
control panels from 2GIG.

GC TOUCH
2GIG EDGE



2GIG products are known for quality and field-proven reliability with more than 5 million security panels and 25 million devices deployed that boast a less than 0.03 percent failure rate – the best in the industry.



**Discover more
about 2GIG
345S sensors**

2GIG-FTD100-345

Flood and Temperature Sensor

345S
SECURITY SENSOR



FEATURES

- Sends a notification if water is detected where it doesn't belong
- Easy installation. No screws or tools needed
- 2GIG 345MHz compatible
- Hot (> 95°F) and Cold (< 41°F) ambient temperature warnings
- Supports encryption via an on-board switch

BENEFITS

- First in the industry to provide dual source protection against water leaks
- Drip notification when placed under a leaking water source. Notification when pooled water is present

TECHNICAL SPECIFICATIONS

Ordering Part Number	2GIG-FTD100-345
Wireless Signal Range	350 ft (106.7m), open air with Wireless Control Panel
Transmitter Frequency	345 MHz
Compatibility	2GIG
Supervisory Interval	70 minutes
Dimensions	2.4" diameter, 1.3" high
Temperature Thresholds	High: 95° F (35°C). Low: 41°F (5°C)
Operating Temperature	32° to 104° F (0° to 40° C)
Operating Rel. Humidity	5 to 95%, non-condensing
Operating Temperature	32°-120° F (0°-49° C)
Relative Humidity	Water-Resistant
Batteries (included)	CR123A 3V Lithium battery
Projected Battery Life	5 years

Specification and availability subject to change without notice.

2GIG 345S sensors offer reliable security coverage for residential and commercial properties to keep clients feeling secure. With sleek, modern designs that seamlessly integrate into any environment, 345S sensors include contact, PIR, glass break, smoke detectors, keyfobs, and more.

2GIG 345S sensors are compatible with the complete 2GIG security ecosystem including the **GC Touch™** and **2GIG EDGE™** security panels.



2GIG.COM

 **2GIG.**
a Nice brand