



345S
SECURITY SENSOR

**Security Sensor with On/Off
Switchable Encryption.**



2GIG-KEY100-345

4-Button Keyfob Remote

The 2GIG® 4-Button Keyfob Remote communicates with the 2GIG Control Panel on the 345 MHz frequency. It gives users the ability to arm and disarm the system before entering the home or after exiting. If there is an emergency, you can activate on the siren and automatically call the central monitoring station. Keyfobs can be programmed to operate the programmable output in the Control Panel. The keyfob operates in encrypted or non-encrypted mode, and runs on a lithium coin battery. It is designed to fit on a key chain, in a pocket, or in a purse.



**Stock half as many SKUs
on trucks.**

Easily choose encrypted/
non-encrypted operation
with an internal switch.
2GIG 345S sensors work
for any installation.

**Complete 2GIG security
ecosystem.**

345S sensors work with
the all-new GC Touch,
revolutionary 2GIG EDGE,
and earlier security &
control panels from 2GIG.

GC TOUCH
2GIG EDGE



2GIG products are known for quality and field-proven reliability with more than 5 million security panels and 25 million devices deployed that boast a less than 0.03 percent failure rate – the best in the industry.



**Discover more
about 2GIG
345S sensors**

2GIG-KEY100-345

4-Button Keyfob Remote

345S
SECURITY SENSOR



FEATURES

- Repeats 2GIG and Honeywell signals on 345MHz frequency
- 24-hour backup battery included
- Repeat indicator in the signal eliminates “repeated signal storm”
- Optional zone programming to supervise Tamper, AC Loss, and Low Battery

TECHNICAL SPECIFICATIONS

Wireless Signal Range	350 ft (106.7 m), open air, with Wireless Control Panel
Code Outputs	Arm; Disarm; Panic; Relay Control
Transmitter Frequency	345.00 MHz (crystal controlled)
Unique ID Codes	Over one (1) million different code combinations
Dimensions (L x W x H)	2.32 x 1.33 x 0.39 in (5.9 x 3.4 x 1.0 cm)
Weight (including battery)	0.65 oz (18.4 g)
Housing Material	ABS Plastic
Color	Black
Operating Temperature	32°-120° F (0°-49° C)
Relative Humidity	5-90% Non-condensing
Battery (installed)	One (1) CR 2025 3V or equivalent Lithium coin batteries
Certification	ETL, FCC, and IC

Specification and availability subject to change without notice.

2GIG 345S sensors offer reliable security coverage for residential and commercial properties to keep clients feeling secure. With sleek, modern designs that seamlessly integrate into any environment, 345S sensors include contact, PIR, glass break, smoke detectors, keyfobs, and more.

2GIG 345S sensors are compatible with the complete 2GIG security ecosystem including the **GC Touch™** and **2GIG EDGE™** security panels.



2GIG.COM

 **2GIG.**
a Nice brand