

LINEAR™

EntryPro 4.3" Telephone Entry



Sensor and Optional Camera

Motion sensors, ambient light sensors and optional HD IP camera.

4.3" Full Color Display

Adjustable back-lighting, an LED screen that is easy to read in direct sun, and customizable text and images.

Optional Internally Mounted RFID Reader

Upgradeable

Out of the box ready for 2 doors and is easily upgradeable with the purchase of a license key.

Intuitive Navigation

A superior user experience with user prompts, tonal cues and flashing keys to guide users through steps.

Built in TTY port is ADA compliant

Out-of-the-Box Ready, Power, then Browse

LINEAR

EntryPRO™

SERIES

EP-402 | Stand-Alone 2-Door Telephone Entry

EP-436 | Networked 36-Door System

- New generation panel looks the same on the outside but is packed with upgraded hardware and software on the inside.
- New software improves network communications.
- 4.3-inch redesigned housing features an improved weatherproofing seal.
- Improved 2-way audio voice calls.

The new line of Linear® EntryPro Telephone Entry solutions are self-contained, fully embedded and browser-managed, allowing for easy deployment and scalability.

Reliable value based Telephone Entry and access control both easy and affordable, with strong security, and an intuitive user interface with no dedicated PC or software required.

EntryPro delivers fast set-up, enhanced features, and scalability with license upgrades. Systems can include one or many integrated doors, gates, reader and credential types enabling

access flexibility while providing convenience for administrators and enhanced security for their residents and facilities.

Manage, monitor, and report on residential accounts, guests and personnel access easily with built-in customized reports and quick-search queries.

EntryPro features are designed for rugged reliability, with added weatherproofing seals and housing for weather-resistant performance. New internal hardware improves system, audio, network communication and performance.

Linear® EntryPro Series

SPECIFICATION COMPARISONS

ITEM	Series – EP-402 / EP-436
Warranty	2 Years Hardware and Software
UL294 Series 6	UL294 Series 6, Attack class 2, FCC
Available Modules	2-Door Module, 2 Door Expansion, 2 Door Add on to Expansion
System Integrity	128 bit Encryption (User database and events) SSL / HTTPS / PHP
Language	English
System Control	Web Browser compatible
Pre Configured Doors Per System	2 on board, expandable to 36 or 64 doors
Max Readers In/Out	2 Per I/O Board
Max Client/Expansion Modules Per Site	32
Distributed Processing	Every module contains database and events
Outputs Per Board	4 Form C SPDT / Dry 5 Amp
Outputs Times	Hours, Min, Sec., by set time and/or repeat quantity,
Notification	Yes, email and SMS event notification
Inputs per board	8- 6 Analog Selectable for type, 2 Pre-assigned (Tamper, Postal)
Input types	NO / NC Parallel Resistor, NO / NC Series Resistor, NO / NC Unsupervised
Predefined Door Configuration	Lock, Prop (Output) REX, Door Position (Input)
Environmental Temperature	-22°F to 149°F (-30°C to 65°C) Humidity: 5% to 95% non-condensing
Power Requirements	9VDC – 15VDC, Includes 12VDC Plug in Power Supply
Remote Management Console	Optional

USER INTERFACE FEATURES

System Fully Web Controllable	Yes
Action Icons	Door Unlock, Toggle, Aux outputs
Alarm Acknowledgement	Yes
Logo Placement	Yes - Ability to place Dealer or End user logo into system

PRODUCT DIMENSIONS

Product Size	EP-402/436: 16.3"(L) x 13.1"(W) x 4.6"(D)
Product Weight	EP-402/EP-436: 14.7 lbs.
Recessed Mounting 1" Trim Ring (PN 720-100123)	Hole Size: 16.5"(L) x 13.25"(W) x 3.5"(D) Outside Dimensions: 18.6"(L) x 15.35"(D)
Recessed Mounting 2" Trim Ring (PN 720-100124)	Hole Size: 16.5"(L) x 13.25"(W) x 3.5"(D) Outside Dimensions: 21.35"(L) x 17.6"(W)

EVENT ACTION	
Event Action Input	Reader Event, Physical Input, Door Position, REX, System Event
Event Action Output	Outputs, Dashboard, eMail, SMS, Back up SD / FTP, Threat level, Video tag
Power (per board)	12VDC from provided DC plug-in power supply - Power for two modules & readers
Total System Access Levels	250
Users per system	EP-402 = 1,000 EP-436 = 10,000
Access cards	5000 / 120000
Cards / Access Levels Per Person	32 / 32
Binary Card Decoder	Yes - 26 - 128 bit with or without facility code, Facility Code Only
User-defined data fields	20 user fields, Flat File Import Option
Database Import Tool	Yes, CSV
DayLight Savings Time "DST"	Automatic, Editable dates if future requirement
SMTP	On / Off Manual, PC Sync
Client Time Zone Configuration	Yes, Each module is selectable
Time specifications (schedules)	250
Time spec groups (Schedule groups)	64
Holidays, Holiday Groups	60, 4 groups
Event history log	50,000 transactions
Transaction Types	Action of any type, Administrator Change Logging "Audit", and System Diagnostic Events.
Archive for transactions	Manual, Automatic daily, Automatic by 90% full
Archive for system configuration files	Manual, Automatic daily
Report Utility	Internal Smart Report Utility
Administration / User Roles	Super for Entire System, Admin designated by doors (building), Customizable by Users
Maximum concurrent web users	25
Maximum defined administrative users	160

ORDERING INFORMATION	Part #	Model #
EntryPro 402	720-200402	EP-402
EntryPro 436	720-200436	EP-436
EXN Door expansion unit	720-100104	EN-EXN
ACM 2-Door Module	720-200105	EP-ACM
License Upgrade: 2-36 Door Networked	720-100145-VL	EC2ENUP
License Upgrade: 36-64 Door	720-100226-VL	EN3664UP



LINEAR

www.linear-solutions.com