



SLE-ANTEX Universal Extended Range Omnidirectional Cellular Antennas

StarLink Omni-X® SLE-ANTEX Series are universal, marine-grade indoor/outdoor multi-band, high-gain omnidirectional antennas, that dramatically increase cellular transmission capability and enable location flexibility, for use with StarLink Cell/IP Communicator models, as well as supporting most other brand radios, including Honeywell®, Telguard®, DSC®, DMP®, etc. **With LTE performance in particular, the antenna has excellent field-proven performance at all cellular bands.** The easy-to-install, maximum performance, wide-band antenna is omnidirectional, does not require aiming, and can be used to increase signal strength in all applications and cellular technologies: LTE, 4G, 3G, CLR, PCS, DCS, AWS, IMT, ISM, WCDMA, cellular, WiFi and WiMax.

All models are sold complete with premium low-loss LMR-type cable and mounting hardware, featuring a compact, long-life UV-stable conical shape antenna and physically resonant design; with an outstanding low VSWR of less than 1.5:1, for maximum radiated power and maximum signal sensitivity. LMR®-type cabling also enables optimum placement of the antenna at the highest possible elevation. Each SLE-ANTEX Series extended range antenna includes an L-bracket with stainless steel U-bolts for pole or wall mounting, ground fault isolation mounting plate (used for commercial fire applications) and premium low-loss cable, available in five lengths, 100', 75', 50', 30' or 4', to easily connect to StarLink and other brand cellular communicators.

FEATURES:

- Increase Cellular Transmission & Mounting Flexibility
- Universal use with StarLink Cellular Communicators & those of other manufacturers
- For Outdoor Use - Marine Grade
- All Applications: LTE, 4G, 3G, CLR, PCS, DCS, AWS, IMT, ISM, WCDMA, cellular, WiFi and WiMax
- Excellent 700MHz LTE performance
- VSWR <1.5:1 for max power and signal range
- RoHS Compliant
- 36-Month Napco Warranty
- **Complete:** Including Mounting Hardware and 4', 30', 50', 75' or 100' premium low-loss LMR-type cable

ORDERING INFORMATION:

SLE-ANTEXT100 Optional extended antenna with 100' ultra low-loss premium cable and complete hardware, including pole mount

SLE-ANTEXT75 As above, with 75' cable

SLE-ANTEXT50 As above, with 50' cable

SLE-ANTEXT30 As above, with 30' cable

SLE-ANTEXT04 As above, with 4' cable

SPECIFICATIONS:

Radiation Pattern:	Omni-Directional
Gain:	4-9dBi
Bandwidth:	VSWR: <1.5: 1 = 695-3000 MHz in all 3G & 4G Bands VSWR: <2.0: 1 = 695-3000 MHz
Impedance:	50 ohms
Max Input Power:	50 watts
Exterior Finish:	Black or white UV stable
Dimensions:	8 7/8" (225 mm) l x 2 3/8" (60 mm) OD
Weight:	Varies with model, cable length chose
RF Connector:	Type N female
PIM:	155dBc
Cable:	Low-loss cable with premium connectors & mounting hardware
Installation:	Included L Bracket with U-bolts for up to 2" pole
Elements:	Copper
Polarization:	Vertical
Wind Rating:	>110 MPH
Warranty:	3 years
Compliance:	RoHS



**StarLink Omni-X
Extended Range
Antennas are for
Universal Use with
StarLink & Most
Other Cellular Radio
Brands, i.e., DSC®,
DMP®, Honeywell®,
Telguard® & more**



StarLink Communications by NAPCO Security Technologies, Inc.
1-800-645-9445 • 1-631-842-9400 • salesinfo@napcosecurity.com