

CL3R/CMR Non-shielded 16 AWG & 18 AWG 300V

CL3R - Nonshielded Conductors
PVC Insulation & Jacket
300 Volt
18 AWG & 16 AWG



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Stranded bare copper to ASTM B-3, B-8, and B-286

Category Insulation Description:

- Color coded Polyvinyl Chloride (PVC)

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC) Includes ripcord

Applications:

- Power limited control circuits
- Wiring of the following systems: Intercom, Security, & Audio
- Suggested Voltage Rating: 300 Volts

Standards:

- NEC Article 725 Type CL3R
- CSA CMG FT-4

Part Number Table								
Part#	Houston Wire & Cable	Gauge	Conductors	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')	Material Weight (KG/KM)
DS91802	HW400.pdf	18	2	0.009	0.015	0.154	17.1	25
DS91803	HW400.pdf	18	3	0.009	0.015	0.166	23.6	35
DS91804	HW400.pdf	18	4	0.009	0.015	0.187	28.9	43
DS91806	HW400.pdf	18	6	0.009	0.015	0.225	42	62
DS91808	HW400.pdf	18	8	0.009	0.015	0.245	56.4	83
DS91810		18	10	0.009	0.015	0.27	69	102
DS91812	HW400.pdf	18	12	0.009	0.015	0.29	84	125
DS91602	HW400.pdf	16	2	0.01	0.015	0.178	25	37
DS91603	HW400.pdf	16	3	0.01	0.015	0.196	39	58
DS91604	HW400.pdf	16	4	0.01	0.015	0.209	45.1	67

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 [™] | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle • St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC