



This high-quality Cat 6 RJ45 Keystone Connector in white is designed for use in all Keystone Wall Plates. The standard RCA front jack connects to Cat5, Cat5e, or Cat6 cables terminated with RJ-45 plugs. The vertical design makes punchdown termination easy, while rear retention caps ensure secure wire connections. It meets Category 6 standards described in TIA/EIA-568-B.2.

## Features & Benefits

|                                                                |                                                                                                                           |
|----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Standard RCA front jack                                        | Connects to Cat5, Cat5e, or Cat6 cables terminated with RJ-45 plugs<br>Rear retention caps ensure secure wire termination |
| Vertical design for easy punchdown termination                 | T658A and T568B wiring labels included                                                                                    |
| Meets Category 6 described in TIA/EIA-568-B.2                  | Insertion and extraction life is 750 Cycles Min                                                                           |
| Jack housing is high-impact, flame resistant plastic, UL 94V-0 | Spring wire is phosphor bronze alloy plated with 50 micro-inch of gold over 100 micro-inches of nickel                    |

## Specifications

### General Info

|                    |              |                   |                                                                     |
|--------------------|--------------|-------------------|---------------------------------------------------------------------|
| Product Line       | On-Q         | Color             | White                                                               |
| UPC Number         | 804428024361 | Country Of Origin | Taiwan, Province Of China                                           |
| Application Sector | Residential  | Standard          | CSA, cULus, RoHS, ANSI/UL 1863, Flame-Retardant Plastic<br>UL 94V-0 |

### Dimensions

|                   |         |                   |         |
|-------------------|---------|-------------------|---------|
| Product Width US  | 0.64 in | Product Height US | 0.87 in |
| Product Length US | 1.28 in |                   |         |

### Technical Information

|                          |                                              |            |      |
|--------------------------|----------------------------------------------|------------|------|
| Termination Style        | Punchdown                                    | Cable Type | Cat6 |
| Environmental Conditions | 0 to 93% (relative humidity, non-condensing) |            |      |