



rexhp

datasheet

High Performance Request-to-Exit

PDK's high-performance request-to-exit device is built to solve any problem your installation may throw at you. The REXHP features a passive infrared sensor with qualified motion analysis that can easily be adjusted for long or short-range applications. Customizable time delays also enable you to provide a premiere security solution for any of your customers needs.



Model

PN: REXHP

Specifications:

Relay

Output: 2C Contact (NC/NO) 24VDC 2A Max
Hold Time: 0.5-64 seconds

Detection Type

Passive infrared

Coverage Range

12x5ft at 7ft high,
30x12ft at 15ft high
Not evaluated by UL

Environment

Operating Temperature: -20°F to 120°F (-29°C to 49°C)
Humidity: 0 - 95% relative humidity
non-condensing

Enclosure

Dimensions: (WxHxD) 7"x1.87"x1.87"
Weight: 0.31 lbs / 5 oz / 142 g
High Impact ABS Plastic Enclosure

Power

12VDC or 24VDC

Manufacturer's Limited Warranty

One to five-year warranty against defects in materials and workmanship. For full details, visit www.prodatakey.com/warranty

Visit www.prodatakey.com or www.prodatakey.com/resources to access marketing, installation, and support resources. For questions about the REXHP, please contact support@prodatakey.com.