



PowerG Where it Matters



Better Range

Stable wireless communication over long range applications



High Strength

ANSI Grade 2 certifications brings extra security and piece of mind



Easy Installation

Easy configuration for smart locks with PowerG wireless communication



Attractive Styling

Three finish options to allow for the best style fit on different door colors



Reliable Connectivity

Reduce truck rolls by eliminating unstable wireless network connections

SPECIFICATIONS

Self-Handing	Supported
Bolt Type	Motorized / Standard deadbolt
Backset	2 3/8" / 2 3/4" Adjustable (60/70mm)
Door Prep	1 1/2" / 2 1/8" (38/54mm)
Door Thickness	1 3/8" ~ 2 1/4" (35-58mm) automatic adjustment
Unlocking Method	PowerG wireless communication (via App and Panel), Button keypad, key, thumb-turn
Code Capacity	User code x 250
Code Length	4-10 digits
Override Key Cylinder	Yes
Cylinder	KW1 keyway
Working Voltage	DC 6V
Battery (Not included)	AA x 4
Working Temperature	Exterior: -31°F to 150°F Interior: 32°F to 140°F
IP Rating	Exterior assembly: IP54
Lockout Mode (Wrong entry limit)	Keypad lockout for 3 minutes after 10 entries of invalid user code
Low Battery Alarm	Yes
Battery Life	Min. 12 months (6 user code unlock events, and 10 unlocking and locking cycles for each day)
Certifications	FCC, IC, ANSI BHMA A156.36 Grade 2, UL10C (20min Fire Rating)
IoT Connection	PowerG
Product Weight	1.6KG/PCS (3.6 LB)
Operating Humidity	Exterior: 100% condensing Interior: 20% – 95% non-condensing