



10B Listed For
3 Hrs Fire Rated Doors

Power Transfer Hinge Application

Installed in the center hinge position of the door, PTH Power Transfer Hinges provide the concealed wires required to transfer power from the frame to electric hardware in the door for control and monitoring capability.

Features

- 5' Ft Cable
- UL10B Listed for 3 Hour Fire Rated Doors. If the hinge you are presently using does not bear the mark 'F' it is not listed for use with fire rated doors.
- 800,000 cycles. 8 times UL test criteria
- Wire Replacement Warranty

PTH-4Q	Four (4) Conductor Power Transfer Hinge 28 gauge - 1-pair 1 Amp, 1-pair 250 mA 4.5" x 4.5" standard weight, 626 Dull Chrome	150.00
---------------	---	---------------

PTH-4Q-DPS	Four (4) Conductor Power Transfer Hinge with Door Status Contact 28 gauge - 1-pair 1 Amp, 1-pair 250 mA @ 12/24V AC/DC Door Status Contact: 250 mA @ 30VDC 4.5" x 4.5" standard weight, 626 Dull Chrome	186.00
-------------------	--	---------------

PTH-10Q	Ten (10) Conductor Power Transfer Hinge 30 gauge - 1-pair 1 Amp, 4-pair 250 mA 4.5" x 4.5" standard weight, 626 Dull Chrome	195.00
----------------	---	---------------

PTH-10Q-DPS	Ten (10) Conductor Power Transfer Hinge with Door Status Contact 30 gauge - 1-pair 1 Amp, 4-pair 250 mA Door Status Contact: 250 mA @ 30VDC 4.5" x 4.5" standard weight, 626 Dull Chrome	226.00
--------------------	---	---------------

SPECIFY FINISH

Add to List

Dull Chrome finish is standard as specified by suffix Q.

To specify special finish, designate finish suffix below in lieu of Q.

C	605 Bright brass	N/C
H	613 Oil rubbed bronze	N/C
P	625 Bright Chrome	N/C

OPTIONS

Add to List

Consult factory for 3 knuckle, and special size, and heavy weight requirements



PTH x 5 Ft Cable



PTH x 5 Ft Cable
And Door Position Switch

DOOR CORE DRILL KIT

NET



The SDC door core drill fixture provides the best method of wire preparation for fire rated or non fire rated particle filled or solid wood doors to accommodate the installation of electrified locksets, exit devices and hinges while maintaining door integrity and rating

- Tested by ITS/ Warnock Hersey for field drilling of rated doors
- Installer may call for inspection of doors to be re-certified after drilling
- Allows for drilling from the hinge side without removing the door from the frame
- Will drill at 20 degrees from center, up or down, from the hinge to the lock prep on a 3'0" door
- Drills doors in 3 minutes
- Easy to use, no experience required
- Includes special 58 inch evacuator drill bit with custom tool room sharpened end
- High speed Delrin bushings ensure long tool life at high speed drilling with little or no noise. Your commercial customers will love the quiet operation in their offices

Discount Not Applicable

7000-DF	Door Core Drill Fixture	572.00 NET
7000-DB	5/16" Custom Replacement Drill bit	124.00 NET