

86 Series - 70/25V Classic Grille In-Ceiling Contractor Speaker

G86TG 8" 70/25V classic grille in-ceiling speaker


G86TCG 8" 70/25V classic grille in-ceiling speaker with
volume control knob

Features

- Classic style white steel grille
- 70/25V transformer with colored leads
- G86TCG features volume control knob centered on grille
- Lifetime warranty



sold individually



Specifications

	G86TG	G86TCG
RMS Power	10W	10W
Max. Power.....	15W	15W
Transformer Type	70/25V	70/25V
Transformer Power Type	5W, 2.5W, 1W, 0.5W, 0.25W & 8 Ohms	5W, 2.5W, 1W, 0.5W, 0.25W & 8 Ohms
Termination Type	Colored leads	Colored leads
Sensitivity (1W/1M).....	90dB	90dB
Maximum SPL (Pax/1M).....	100dB	100dB
Driver Impedance	8 Ohms	8 Ohms
Magnet.....	5 oz. ferrite	5 oz. ferrite
Frequency Response Range.....	85Hz ~ 20kHz	85Hz ~ 20kHz
Dispersion @ 1000Hz.....	120° Conical	120° Conical
Driver	8" paper cone woofer, 8" dual cone tweeter	8" paper cone woofer, 8" dual cone tweeter
Speaker Dimensions.....	13" (Dia.) x 3.5" (D)	13" (Dia.) x 3.5" (D)
Mounting Dimensions	11.3" (Dia.)	11.3" (Dia.)
Minimum Mounting Depth.....	2.7"	2.7"
Weight	2.7 lbs.	2.7 lbs.
Material.....	Grille: steel	Grille: steel
Color.....	Off-White	Off-White

NDA
A
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

Speco Technologies is constantly developing and improving products.
We reserve the right to modify product design and specifications without notice
and without incurring any obligation. Spec Rev. 11/4/14

Optional Accessories



TS8
T-Bar Bridge for
Ceiling Support



STH8
Heavy Gauge
Steel Backcan